## CLASSIFIED INDEX OF TECHNICAL OIL MISSION REEL 252

	Page
ALCOHOL synthesis by the gas recycle process	17-18
Do. synthesis, Leuna discussions of	15
ALCOHOLS, fatty acids, sulfonates, conversion of gas synthesis	
products into	15
AMMONIA catalysis, theory of	30
AMMONIUM chloride, replacing of in hydrogenation of Ruhr coal	144_
Do. chloride, substitutes for	66-67
ARCMATICS, knock testing with different mixtures of	21-22
ASPHALT tests, correlation of, with 1.t. car. results	68
BAUXITE residues from Al203 production	30-32
BITUMEN, primary, conversion of to heavy oil	28
Do. , primary, rotating autoclave experiments on extraction of	81-82
Do. production, effect of age of coal on primary	75-76
BMW Flugmotorenbau, G.m.b.H., report of a visit to	20
BRIQUETTING, large scale tests in Blechhammer	. 88
Do. , use of hydrogenation pitch in	86-88
Do. , use of hydrogenation residues in	32
CATALYST, coal as, in hydrogenation of pitch-tar mixtures	74-75
CATALYSTS, char-iron, comparison of hydrogenation with different	74
Do. for pitch-tar mixtures, rotating autoclave tests for	75
Do. , liquid phase	54-55
Do. , liquid phase, in rotating autoclaves	89-90
CAVIAR formation with Rhenish lignite in 10 1. converters	50
Do. , x-ray investigation of	82
CAVIAR-LIKE deposits in first converter, fuel oil production	•
from Silesian coal	47-48
COAL, bituminous, comparison of upgrading processes	22-27
Do. extract, processing of in Welheim	76-78
COBALT catalyst, available supplies of	16-17
COLD paste, Scholven experience with injection of	67
CONVERTER, fifth, experience with	45-46
Do. temperatures, regulation of	33
CORONENE in hydrogenation of cold catchpot bottoms	146
CRACKING of hydrogenation gas	29-30
CREOSOTE oil S, processing of	103
CRUSTS, preheater, chemical composition of	34-35
DEHYDROGENATION, hydrogenation, and methanol synthesis,	
instrumentation in	33
DIESEL OILS, ignition accelerators for	
DRYING of coal in Lievin and Bethune	32
ELECTRODE coke and fuel oil production, mild hydrogenation for	68-70
EMPLOYMENT of foreign help	33
EQUILIBRIA, hydrocarbon, in gas synthesis	11

	Page
FATTY acids, alcohols, sulfonates, conversion of gas synthesis	
products into	15
FIFTH converter, experience with	45-46
FILTRATION, H.O.L.D., Poelitz	88-89
Do. , H.O.L.D., tests	59 <b>-</b> 60
Do. of hydrogenation products, tests of	8 <b>5-8</b> 6
Do. tests in 1937	82-83
FLY ash, hydrogenation tests with	146
FOAM process, operations of 1.5 m.3 plate reactor for	
hydrocarbon synthesis	11-15
Do. , organic chemicals in the water stream of	
synthesis by	9-11
Do. and gas recycling, comparison of, gas synthesis	16
FUEL oil and electrode coke production, mild hydrogenation for	68-70
Do. discussions in Gelsenberg	67
Dot arrendered my demonstrate	·
CAS recycling and foam processes, comparison of, gas synthesis	16
Do. synthesis, synol process, discussion of	19
GASIFICATION, composition of, in 600 atm. heavy oil process	66
GASOLINE, aviation, cost of production from bituminous coal,	
hard pitch and pitch-tar mixtures, Poelitz, 6/11/41	Ļ
Do. , aviation, costs of production from Romanian crudes	
in Poelitz, 10/30/41	<b>5-8</b>
No. aviation discussion of	20
Do. , aviation, Scholven VT-345, specifications for	21
Do. , aviation, testing of	19-20
Do. , octane numbers of light fractions	20
GELSENBERG coal, hydrogenation at 600 atm.	68
Do. , inspection report in	33
HEAT EXCHANCE, H.O.L.D.	91-101
Do. , paste	33
H.O.L.D., comparison of results of analyses of	88
Do. filtration, Poelitz	88-89
Do. filtration tests	58-59
Do. heat exchange	91-101
Do. samples, testing of	89
HYDROCARBONS, liquid, patent application from gaseous carbon	_
compounds, by Sacher	9
HYDROGENABILITY of coal	53
HYDROGENATION at 600 atm. of Gelsenberg coal	62
Do. , bituminous coal, addition of sodium sulfide to	72-73
Do. , comparison of, with different char-iron catalysts	74
Do. , dehydrogenation and methanol synthesis, instru-	
mentation in	33
Do. , destructive, translation (into German) of a	•
Russian article	30
Do. gas, cracking of	29-30
Do. materials and products, tables of	51-53
Do. , mild, for fuel oil and electrode coke production	68-70
Do. products, filtration of, tests of	85-86
Do. products, separation of solids from	84-85
Do. results of Silesian coal	55-56

		Lage
HYDROGENA TTON	to fuel oil, new method of	748
Do.	of bituminous coal coking tar with addition of	4.
	bituminous coal	56
Do.	of cold catchpot bottoms with pilot plant	•
	experience, Silesian coal	46
Do.	of German petroleum	62
Do.	of high-C bituminous coal	74
Do.	of mixtures of Silesian coal with Silesian	
	bituminous coal tar at 700 atm.	73-74
Do.	of older coals with SnO and chlorine	61
Do.	of Puertollano coal, rotating kiln tests of	55
Do.	of Ruhr coal, replacing of ammonium chloride in	44
Do.	of Scholven coal with iron catalysts and chlorine	70-72
Do.	of Silesian coal to gasoline and middle oil at	•
	600 atm. in 10 1. conv.	33-34
TONTETON ACCO	elerators for Diesel oils	1-4
	[ON in hydrogenation, dehydrogenation and methanol	
TUQITONENIN II	synthesis	33
TPON antalmet	t, replacing cobalt with	16
THOM CAUSTASI	ts and chlorine, hydrogenation of Scholven coal with	70-72
	ts, hydrocarbon synthesis with	9
***************************************	the control to the description models on	88
KILINING OF U	igh-asphalt hydrogenation residues	00
	curves, by the Oppau process, comparability with	21
	percharge	
	curves of alcohol-gasoline mixtures	21
	curves of gasolines	20
Do. testing	with different mixtures of arountics	21-22
LIQUID phase	catalysts	54-55
Do. phase	hydrogenation, reduction of molybdenum consumption in	70
Do. phase	preheater, reduction of load in	35-53
	extract, extraction with phenol	78-81
Do. ,	extraction with, in; preliminary report on phenol	81
METHANOT. sund	thesis, hydrogenation and dehydrogenation,	
	trumentation in	33
	onsumption, reduction of in liquid phase hydrogenation	70
PRINCIPIL L	drogenation of German	62
	eriments of steam distilling of	102
	action with, Lutzkendorf extract	78-81
	action with in Lutzkendorf, preliminary report on	81
	action, separation of residual oils in	102
	t of production of aviation gasoline from bituminous	705
	l, hard pitch and pitch-tar mixtures, 6/11/41	4
	t of production of aviation gasoline from Romanian	4
	des in, 10/30/41	5-8
	L.D. filtration	88-89
	pection trip	62-66
	rusts, chemical composition of	34-35
	eduction of load in liquid phase	35-13

		Page
PUERTOLL	ANO coal, rotating kiln tests of hydrogenation of	55
RESIDUAL	oils, separation of, in phenol production, hydrogenation, use of in briquetting	102 32
ROMANTAN	crudes, costs of production of aviation gasoline from,	
TO BEN TEN	in Poelitz, 10/30/41	5-8
SCHOLVEN	coal, detailed discussion of pilot plant hydrogenation of	48
Do.	coal, rotating autoclave tests with	49-50
Do.	experience with injection of cold paste	67
SILESIAN	coal, fuel oil production from, caviar-like deposits	47-48
<b>5</b> -	in first converter coal, hydrogenation of in 10 1. conv.	47-40
Do.	coal, hydrogenation of to gasoline and middle oil at	44
Do.	600 atm. in 10 1. conv.	33-34
Do.	coal, hydrogenation of, to heavy oil excess	56-57
Do.	coal, hydrogenation results of	55
Do.	coal, pilot plant experience with hydrogenation of	1.2
	cold catchpot bottoms	76
Do.	coal, rotating autoclave tests with	50 ·
SODIUM a	mulfide, addition of to bituminous coal hydrogenation	72-73 84-85
SOLIDS,	separation of, from hydrogenation products G hydrogenation and saturation of the liquid phase	04-07
SPLITTIN	middle oil	70.
STRAM. h	chavior of, at 450° C. and 700 atm.	48-49
SILFUR.	preliminary results of hydrogenation with	57-58
SUPERCHA	RGE curves, calculation of	20
SYNOL DI	ocess, discussion of	19
SYNTHESI	S, alcohol, by the gas recycle process	17-18
Do.	, alcohol, Leuna discussions of	15
Do.	, gas, comparison of gas recycling and foam processes	16
Do.	, gas, conversion of products into alcohols, fatty	15
	acids, sulfonates	ű
Do.	, gas, hydrocarbon equilibria in	17
Do.	, gas, test , hydrocarbon, operations of 1.5 m.3 plate reactor	
Do.	foam process for	11-15
Do.	, hydrocarbon, with iron catalysts	9
Do.	, organic chemicals in the water stream of, by foam	
	process	9-11
<b>=45 1</b> /4	budge on a side of with addition of	
	tuminous coal coking, hydrogenation of, with addition of	56
	ruex, hydrogenation of	55-56
Do. 1	t.car., increased use of	33
TTH cate	chpot bottoms Kipp filter tests	59-60
Do. car	tchpot bottoms rotating filter tests	60-61
	irogenation of Deuben tar	61-62
	nrocessing of coal extract in	76-78
LINCI LITETIM	NECCORD OF OT COST SITTECT (I)	: /