

I. C. 7415,  
November 1947.

INFORMATION CIRCULAR

UNITED STATES DEPARTMENT OF THE INTERIOR - BUREAU OF MINES

GASIFICATION OF SOLID FUELS IN GERMANY BY THE LURGI, WINKLER, AND  
LEUNA SLAGGING-TYPE GAS-PRODUCER PROCESSES<sup>1/</sup>

By William W. Odell<sup>2/</sup>

CONTENTS

	<u>Page</u>
Introduction.....	3
Acknowledgments.....	3
The Lurgi pressure-gasification process.....	5
Major reactions involved.....	5
Effect of pressure upon the composition of the gas.....	7
The Lurgi gas-generating plant and its operation.....	9
Operating results making gas in the Lurgi pressure generators at Böhlen, Germany.....	12
Capacity of the Lurgi generator and standard water-gas sets compared.....	14
Braunkohle used in Germany.....	16
Other reported data on the Lurgi gas-making process.....	16
Gasification at moderate pressure below 10 atmospheres of a brown coal of low tar content.....	17
Gasification of carbon at different pressures at 1,340° F. (theoretical values).....	18
Results obtained in a small generator with an internal sec- tional area of approximately 10.765 square feet and using various fuels.....	19
Results obtained under test conditions on the small generator with an internal diameter of approximately 4 feet and which are said to be "average results".....	19
Heat balance of pressure-gas operation of a small test genera- tor using screened, partly dried, brown coal containing 27 percent moisture.....	21
Operation with various coals at 20 atmospheres absolute pres- sure.....	21
Factors relating to comparative costs.....	22
Relative costs of materials used in making water gas and pres- sure-process gas.....	23
Relative costs of materials used in making carbureted-water gas and Lurgi pressure-process gas.....	24
Annual costs.....	26

<sup>1/</sup> The Bureau of Mines will welcome reprinting of this paper, provided the following footnote acknowledgment is used: "Reprinted from Bureau of Mines Information Circular 7415."

<sup>2/</sup> Former chief, Synthesis Gas Production Division, Office of Synthetic Liquid Fuels, Bureau of Mines, Washington, D. C.

CONTENTS (Cont'd.)

	Page
The Winkler generator and gasification process.....	27
Kind of fuel adapted for use in a Winkler generator.....	28
Sizes and range in sizes of fuel used.....	28
Softening point of the fuel ash.....	28
Reactivity.....	29
Tar content of the fuel.....	29
Some results of operation of the Winkler process.....	29
Miscellaneous notes on operation at Zeitz.....	31
Operations of Winkler process at Leuna, Germany.....	32
Notes on the use of air instead of oxygen in making gas in a Winkler generator.....	33
The Leuna slagging-type gas producer.....	34
Composition of producer gas from coke.....	35
Remarks.....	37
The cost of oxygen.....	38
Summary and conclusions.....	39
Appendix.....	42
Data relating to the production of city gas and liquid fuel from oven gas and water gas in Fischer-Tropsch converters.....	42
Description of plant and proposed operating procedure.....	43

ILLUSTRATIONS

Fig.		Following page
1.	Variation of the logarithm of the equilibrium constant ( $\log_{10}K$ ) with temperature for several reactions involving $O_2$ , $H_2$ , $H_2O$ , C (graphite), $CO$ , $CO_2$ , and $CH_4$ .....	6
2.	Variation with temperature in composition and calorific value of water gas made from steam and carbon under equilibrium conditions (approximations from equilibrium data).....	6
3.	Variation with pressure in composition and calorific value of water gas made when steam alone is reacted with carbon at 1,832° F. (1,000° C.), approximations from equilibrium values.....	6
4.	Variation with pressure in composition and calorific value of raw gas made by gasifying reactive coal at 1,540° F. (1,000° K.) and employing oxygen and steam as gas-making fluids.....	6
5.	Variation with pressure in composition and calorific value of raw gas as made in practice from brown coal and employing oxygen and steam as gas-making fluids.....	8
6.	Diagram of a Lurgi high-pressure generator.....	8
7.	Diagram of a Winkler generator.....	26
8.	Comparative costs of gas-making materials required for making ordinary water gas and Winkler gas.....	34
9.	Diagram of a Leuna slagging-type gas producer.....	34
10.	Comparative costs of materials required in making ordinary water gas and slagging-type producer gas.....	35
11.	Cost of oxygen used in making gas, with variously priced oxygen, using 100 to 300 cubic feet of it per 1,000 cubic feet of gas made.....	38
12.	Diagram of the flow of gases through the conversion and gas-treating units of a Fischer-Tropsch plant used in making city gas.....	42

Ger  
 which di  
 are of p  
 arise:  
 so, with  
 were dev  
 utilizat  
 characte  
 the Unit  
 develope  
 the part  
 characte  
 tion. T  
 operatio  
 sidered

1.  
 2.  
 3.

Each of

For  
 along wi  
 ally enc  
 from air  
 a plant  
 recently

The  
 suitable  
 generate  
 gasifyin  
 and the  
 of the

Op  
 the Tec  
 vocally  
 those p  
 basic o

Th  
 Germany  
 on an i  
 cal Oil  
 to the