

The average temperatures of the outer and inner retort tubes at different elevations above the bottom of the furnace are shown in table 8. It should be noted that at points C and D, which are the hottest sections of the retort, the gradient across the annular section is 660°F. to 900°F., varying with its thickness.

TABLE 8. - Average temperature gradients across reaction zone, Grand Forks pilot plant.^{1/}

Run number	1	2	3	4					
Width of annulus, inches ^{2/}	4	3	3	3					
Optical pyrometer observation points	Tube temperatures, °F.								
Point	Location ^{3/}	Outer	Inner	Outer	Inner	Outer	Inner	Outer	Inner
A	2.25	1,790	740	1,750	1,125	1,915	1,075	1,905	1,090
B	4.25	1,795	800	1,760	1,845	1,845	1,870	1,870	1,870
C	6.25	1,770		1,860	1,160	1,885	1,215	1,900	1,200
D	8.25	1,740	830	1,780	1,120	1,760	1,100	1,780	1,105
E	10.25	1,700		1,740		1,735		1,695	
F	12.25	1,650	625	1,630	890	1,620	735	1,570	780
G	14.25	1,585	545	1,540		1,520		1,470	

^{1/} Outside retort tube temperatures measured with optical pyrometer.

Inner retort temperatures measured with chromel-alumel thermocouples at similarly located levels.

^{2/} Width of reaction zone space between outer and inner retort tubes.

^{3/} Distance, in feet, above bottom of retort shell.

The average static pressures in the reaction zones in relation to flow of materials during runs 1, 2, and 3 are given in table 9. A more detailed record of static pressure in the retort unit is given in table 10, which records the average pressures throughout the system for each period of run 4.

Properties of Chars and Dusts

The proximate and ultimate analyses of chars obtained from the main outlet at the bottom of the lower annulus are given in table 11. As noted in the footnotes of this table, considerable trouble was experienced in determining the true ash content of the higher ash samples because of the formation of sulfates and because of the presence of magnetic material. The ash content reported has not been corrected for sulfates or carbonates.

A study of the analyses of chars and dusts obtained during run 3 is given in table 12. The char is defined as the residue collected from the lower annulus. The blow-over dust is the residue carried through the gas ports at the junction of the upper and lower annuli, and the dust is carried out of the system with the gas. It should be noted that the ash concentrates in the smaller sizes.

TABLE 9. - Static pressure and flow of materials in the reaction zones, Grand Forks pilot plant.

Run and period	1A	1B	2A	2B	2C	2D	2E	3A	3B	3D	3F	3G	3H
Mcf per hour	8.5	10.1	11.0	12.3	13.6	14.9	15.8	7.8	15.3	13.0	12.3	12.2	12.6
Charging dome	9.3	20.8	18.3	24.8	31.3	21.4	18.4	14.7	12.5	13.4	14.7	13.6	14.2
Char discharge	8.4	9.4	5.9	7.3	8.4	7.6	10.0	8.3	10.4	8.5	6.2	5.3	7.6
Gas offtake	1.2	1.7	2.4	2.6	2.6	3.3	2.5	3.6	1.2	2.3	2.8	1.8	2.1
Drop through upper annulus	8.1	19.1	15.9	22.2	28.7	18.1	15.9	11.1	11.3	11.1	11.9	11.8	12.1
Drop through lower annulus	7.2	7.7	3.5	4.7	4.8	4.3	7.5	4.7	9.2	6.2	3.4	3.5	5.5
Width of reaction zone	4	4	3	3	3	3	3	3	3	3	3	3	3
Length of upper annulus	153	153	138	138	138	138	128	128	128	128	128	128	128
Length of lower annulus	52	52	60	60	60	60	60	60	60	60	60	60	60
Process steam to upper annulus	0	165	100	65	65	0	0	500	50	50	50	0	0
Steam from coal in upper annulus	224	258	165	181	202	304	277	150	250	197	202	202	227
Total steam to upper annulus	224	423	265	246	267	304	277	650	300	247	252	202	227
Process steam to lower annulus	400	400	200	200	200	200	250	300	300	300	150	150	200

1/ Gas outlet ports were increased by shortening upper annulus 10 inches.

TABLE 10. - Static pressures in retort unit, inches of water, run 4, Grand Forks pilot plant. 1/

R. I. 4128

TABLE 10. - Static pressures in retort unit, inches of water, run 4, Grand Forks pilot plant. 1/

Period number	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
Furnace pressure	0.50	0.025	0.027	0.021	0.025	0.025	0.013	0.025	0.022	0.022	0.019	0.016	0.013	0.016	0.016
Air and Poc to recuperator	1.00	1.04	1.04	1.07	1.07	1.04	1.02	1.02	.99	.99	1.00	1.05	1.00	1.00	.97
Air and Poc to furnace	0.50	.50	.55	.58	.58	.60	.55	.49	.46	.46	.46	.52	.50	.55	.47
Outlet of furnace 2/	.0	.0	-.08	-.52	.85	-1.27	-.16	-.16	-.21	-	-.25	-.11	-.13	-.12	-.08
Poc out of recuperator	-2.50	-2.59	-2.59	-2.52	-2.56	-2.53	-2.48	-2.48	-2.51	-2.61	-2.51	-2.56	-2.59	-2.64	-2.46
Inlet to fan	-2.81	-2.89	-2.81	-2.78	-2.84	-2.78	-2.76	-2.86	-2.86	-2.92	-2.94	-2.90	-2.94	-2.94	-2.73
Outlet of fan	1.24	1.41	1.35	1.45	1.41	1.41	1.43	1.35	1.35	1.29	1.32	1.35	1.29	1.36	1.61
Char discharge	7.13	6.96	6.16	7.50	8.03	7.26	7.46	6.66	5.70	5.16	5.33	4.13	6.56	8.60	9.65
Charging dome	16.93	17.63	17.96	13.83	13.76	13.16	13.36	28.86	17.43	18.20	16.03	29.40	23.60	29.90	27.20
Gas leaving retort	2.30	2.03	2.03	2.06	2.70	2.06	2.33	2.70	2.13	2.03	2.13	2.00	2.13	3.40	2.40
Drop thru upper annulus	14.63	15.60	15.93	11.77	11.06	11.10	11.03	26.16	15.30	16.17	13.90	27.40	21.47	26.50	24.80
Drop thru lower annulus	4.83	4.93	4.13	5.44	5.33	5.20	5.13	3.96	3.57	3.13	3.20	2.13	4.43	5.20	7.25
After water separator				-.33	.85	-1.18	-1.29	-2.12	-1.00	-1.43	-.80	-2.33	-2.75	-4.4	-1.41

1/ Average of 24-hour period.

2/ Gas sample line connected to this circuit. Pressure data are not reliable.

TABLE 11. - Proximate and ultimate analyses of chars from Grand Forks pilot plant. 1/

Run and period	Condition	Pittsburgh lab. No.	Proximate, percent		Ash	Ultimate, percent			B. t. u. per pound	Softening temp. ash, °F.		
			Moisture	Volatile matter		Fixed carbon	Hydrogen	Carbon			Nitrogen	Oxygen
Pre.-A	1	C-36716	11.0	14.4	55.0	19.6	59.7	0.7	16.7	0.3	9,400	
	2		16.2	61.7	22.1	2.0	67.1	.8	7.7	.3	10,570	
	3		20.8	79.2		2.5	86.1	1.0	10.0	.4	13,560	
Pre.-B	1	C-36715	5.5	15.5	56.3	22.7	61.7	.8	11.8	.4	9,720	
	2		16.3	59.7	24.0	2.1	65.3	.8	7.4	.4	10,280	
	3		21.5	78.5		2.7	85.8	1.0	10.0	.5	13,520	
1-A ...	1	C-44346	2.9	12.8	68.5	15.8	74.9	.8	5.5	.9	11,820	
	2		13.2	70.5	16.3	1.8	77.1	.8	3.1	.9	12,170	
	3		15.8	84.2		2.2	92.1	1.0	3.6	1.1	14,540	
1-B ...	1	C-44347	2.9	12.8	69.3	15.0	75.2	.8	5.9	.8	11,930	
	2		13.2	71.4	15.4	2.0	77.4	.8	3.6	.8	12,280	
	3		15.6	84.4		2.4	91.5	1.0	4.1	1.0	14,520	
1-C ...	1	C-44348	2.6	11.5	68.3	17.6	72.3	.8	7.0	.4	11,240	
	2		11.8	70.2	18.0	1.7	74.2	.8	4.8	.5	11,530	
	3		14.3	85.7		2.0	90.5	1.0	5.9	.6	14,070	
2-A ...	3/	C-52389	1.3	10.3	61.0	27.4	69.1	0.6	2.0	10,743	2,450	
2-B ...	3/	C-52390	1.2	9.7	55.1	34.0	65.6	.4	3.0	10,232	2,440	
2-C ...	3/	C-52391	1.2	8.8	53.7	36.3	63.6	.4	2.9	9,851	2,430	
2-D ...	1	C-52392	1.2	8.8	70.6	19.4	75.9	.7	1.0	1.5	11,810	2,400
	2		8.9	71.5	19.6	1.4	76.8	.7	.0	1.5	11,950	
	3		11.1	88.9		1.7	95.6	.8	.1	1.8	14,870	

See footnotes on page 39.

R. I. 4128

TABLE 11. - Proximate and ultimate analyses of chars from Grand Forks pilot plant. 1/ (cont'd.)

Run and period	Condi- tion 2/	Pittsburgh lab. No.	Proximate, percent		Ash	Ultimate, percent			B.t.u. per pound	Softening temp. ash, °F.		
			Moisture	Volatile matter		Fixed carbon	Hydrogen	Carbon			Nitrogen	Oxygen
2-E ...	3/	C-52393	1.2	9.1	67.1	22.6	1.4	73.3	.6	1.5	11,380	2,470
3-A ...	4/	C-56892	1.4	10.2	72.8	15.6	1.9	76.6	.7	.5	12,040	2,510
3-G ...	4/	C-56891	1.1	6.3	69.7	22.9	1.1	74.4	.5	1.9	11,390	2,490
4-H ...	5/	C-57636	1.1	7.1	67.6	24.2	1.3	73.1	.5	2.1	11,300	2,560

Note: Proximate analyses of all samples were made by standard A.S.T.M. methods for coal and coke. It has been found in a later study, that more than 95 percent of the sulfur in the char has been retained in the ash as compounds of SO₂. The ash values are subject to correction to the extent of the SO₂ present, else the sulfur values are included twice in the analyses. The true ash in most cases may be estimated by using as the basis of correction, the heating value of the char on the moisture- and ash-free basis, as 14,200 B.t.u. per pound. The fixed carbon value of the char, being determined by difference in the standard method, is subject to correction by the amount of the SO₂ in the as-determined ash.

1/ Composite increment sampling aggregating about 2.75 percent of char removed. Samples from preliminary runs through run 1-C analyzed by standard methods. No corrections were made for sulfates in ash or magnetic residues in ash.

2/ Condition: (1) as received, (2) moisture-free, (3) moisture-and-ash free.
 3/ Analyses reported on as-received basis. Fixed carbon, ash, and oxygen values have not been corrected for presence of magnetic iron in the samples. Subsequent tests indicated magnetic material may range from 3 to 7 percent.

4/ Analysis on as-received basis. The sulfur content of the ash was determined as SO₂. In run 3-A, sulfur - 1.4 percent; in 3-G, 4.75 percent. The CO₂ content of sample 3-A - 2.81 percent, and in 3-G, 2.39 percent.

5/ Analysis on as-received basis. The ash was found to contain 5.04 percent sulfur, analyzed as SO₂. Sample contained 2.44 percent CO₂, as-received-basis.

R. I. 4128

TABLE 12. - Proximate analyses of residues, run 3, Grand Forks pilot plant.^{1/}

Run and period	Condition ^{2/}	Char				Blow-over dust				Dust in gas	
		Proximate, percent		Magnetic material, percent ^{3/}	Proximate, percent		Magnetic material, percent ^{2/}	Ash, percent	Magnetic material, percent ^{3/}	Ash, percent	Magnetic material, percent ^{3/}
		Volatiles matter	Fixed carbon		Volatiles matter	Fixed carbon					
3-A	2	10.2	72.9	16.9	3.4	14.3	51.7	34.0	3.2	19.1	1.1
	3	12.3	87.7			21.7	78.3				
3-B	2	7.5	72.5	20.0	3.6					33.2	.9
	3	7.9	92.1								
3-C	2	7.3	68.2	24.5	4.4	7.4	33.7	58.9	2.2	28.2	2.1
	3	9.7	90.3			18.0	82.0				
3-D	2	7.6	70.6	21.8	5.2	6.0	24.2	69.8	2.3	31.3	2.1
	3	9.7	90.3			19.9	80.1				
3-E	2					9.0	60.0	31.0	1.1		
	3					13.0	87.0				
3-F	2	7.0	72.2	20.8	5.4	6.4	36.1	57.5	1.6	33.0	1.8
	3	8.8	91.2			15.1	84.9				
3-G	2	6.1	70.9	23.0	6.0	4.9	36.2	58.9	1.6	34.0	1.1
	3	7.9	92.1			11.9	88.1				
3-H	2	7.1	74.1	18.8	4.1	5.7	35.2	59.1	2.5		
	3	8.7	91.3			13.9	86.1				
3-J	2					6.4	32.8	60.8	2.5		
	3					16.3	83.7				

^{1/} Analyses made at Golden on residues with magnetic material removed.

^{2/} Condition: (2) moisture-free, (3) moisture and ash free.

^{3/} Magnetic material was removed by passing over an electromagnet. It is not entirely magnetite and contains an undetermined amount of carbon.

The size consist and proximate analyses of chars and dusts obtained from the runs on the Golden pilot plant are given in table 13. The larger pieces of char are predominantly high in ash, which is probably due to unchanged pieces of slate and shale. With this exception, the ash increases in the smaller sizes. The size consist and ash content of dusts carried out with the gas in the large plant are shown in table 14. This study also shows that the ash concentrates in the smaller sizes.

TABLE 13. - Physical and chemical properties of chars and dusts from Golden gasification runs 10, 11, and 12.

Run and period	Char from retort					Dust in gas				
	Size of frac-tion ^{2/}	Per-cent of frac-tion size	Proximate analy-sis percent ^{1/}			Size of frac-tion ^{2/}	Per-cent of frac-tion size	Ultimate analy-sis percent ^{1/}		
			Vol. mat.	Fixed carbon	Ash			Vol. mat.	Fixed carbon	Ash
10-A ...	+0.530	3.0				16 x 30	8.0			
	+.263	28.0				30 x 60	30.6			
	+.131	44.0				60 x 100	13.8			
	+.065	14.0				100 x 200	16.0			
	-.065	11.0				-200	31.6			
	Composite	3/	8.2	76.3	15.5	Composite	4/	25.1	19.1	55.8
10-B ...	+0.530	3.0				16 x 30	12.4			
	+.263	35.0				30 x 60	31.3			
	+.131	30.0				60 x 100	11.7			
	+.065	14.0				100 x 200	12.3			
	-.065	18.0				-200	32.3			
	Composite	4/	11.8	67.3	20.9	Composite	3/	23.0	30.5	46.5
11-A ...	+0.530	4.0	3.4	14.7	82.9	+16	0.3	15.1	62.5	22.4
	+.263	30.0	9.0	57.6	33.4	16 x 30	13.6	17.6	53.8	28.6
	+.131	30.0	10.5	67.9	21.6	30 x 60	28.5	19.1	44.4	36.5
	-.131	36.0	14.6	52.0	33.4	60 x 100	12.9	22.3	30.3	47.4
	Composite	3/	11.0	59.1	29.9	100 x 200	13.5	23.9	21.3	54.8
						-200	31.2	25.8	10.7	63.5
					Composite	4/	22.0	30.4	47.6	
12-A ...	+0.530	1.8	4.2	24.6	71.2	16 x 30	3.3	19.4	58.8	21.8
	+.263	30.9	7.0	73.8	19.2	30 x 50	18.6	19.5	60.4	20.1
	+.131	35.2	7.8	78.0	14.2	50 x 100	23.4	21.7	51.0	27.3
	+.065	12.4	8.3	77.3	14.4	100 x 200	18.7	24.0	39.9	36.1
	-.065	19.7	12.9	58.0	29.1	-200	36.0	25.0	26.9	48.1
	Composite	3/	11.3	70.0	18.7	Composite	3/	26.5	38.8	34.7
12-B ...	+0.530	1.8	3.9	15.1	81.0	16 x 30	3.7	18.7	50.7	30.6
	+.263	16.6	7.8	66.1	26.1	30 x 50	24.7	15.9	60.1	24.0
	+.131	53.5	7.8	78.1	14.1	50 x 100	23.6	18.7	48.8	32.5
	+.065	19.9	9.1	76.5	14.4	100 x 200	16.7	22.1	33.7	44.2
	-.065	28.2	13.0	59.4	27.6	-200	31.3	24.8	20.3	54.9
	Composite	3/	10.5	70.0	19.5	Composite	3/	21.1	39.8	39.1

TABLE 13. - Physical and chemical properties of chars and dusts from Golden gasification runs 10, 11, and 12. (cont'd.)

Run and period	Char from retort					Dust in gas				
	Size of fraction ^{2/}	Per cent of frac. size	Proximate analysis percent ^{1/}			Size of fraction ^{2/}	Per cent of frac. size	Ultimate analysis percent ^{1/}		
			Vol. mat.	Fixed carbon	Ash			Vol. mat.	Fixed carbon	Ash
12-C ...	+0.550	0.2	3.9	34.8	61.3					
	+0.263	8.5	7.5	74.3	18.2					
	+0.131	38.8	10.2	76.5	88.2					
	+0.065	21.0	11.0	74.6	14.4					
	-0.065	31.5	17.6	52.5	29.9					
	Composite	3/	11.6	72.1	16.2					

- 1/ Proximate analyses on moisture-free basis. Analyses of sized fractions of char and dust by Golden laboratory.
- 2/ Standard square-mesh screen opening, in inches. Numbered sieve sizes are U. S. standard series.
- 3/ Analyses of composite samples by Pittsburgh laboratory.
- 4/ Analyses of composite samples by Golden laboratory.

TABLE 14. - Size consist and ash content of dusts, Grand Forks plant.

Screen size ^{1/}	8	16	30	50	100	200	-200
	Run 2-E			Blow-over dust			
Percentage retained	3.9	10.1	25.1	30.3	17.6	8.6	4.4
Ash content percent ^{2/}	3/	15.73/	34.7	63.6	74.2	76.7	80.5
	Run 2-C			Dust with gas			
Percentage retained	0.0	0.0	0.4	12.2	40.8	27.5	19.1
Ash content percent ^{2/}				39.1	42.2	45.4	56.3
	Run 2-D			Blow-over dust			
Percentage retained	0.8	3.7	25.5	39.5	18.1	8.7	3.7
Ash content percent ^{2/}		18.2	40.7	59.6	64.5	64.2	71.9
	Run 2-D			Dust with gas			
Percentage retained	0.0	0.0	0.8	31.6	31.8	21.2	14.6
Ash content percent ^{2/}			36.3	40.4	42.8	45.0	48.2
	Run 4-H			Blow-over dust			
Percentage retained	5.0	8.2	15.5	32.0	24.3	10.7	4.5
	Run 4-H			Dust with gas			
Percentage retained	0.0	0.2	0.1	4.0	19.8	28.2	47.7

- 1/ Numbered square-mesh sieve sizes, fine series.
- 2/ All samples analyzed on moisture-free basis.
- 3/ Nos. 8 and 16 increments combined for analysis.

gross l
meter,
meter.
period.
over th
person
gases n
analyse
iod whe

At
holder
was som
tion of
plate g
withdra

At
a small
gas lin
interva
ficient
ployed
used fo
pulative
flowing
foot re
of gas
ple. W
cubic f
mately
ceiver
samplin
absorbe

Tal
12 in th
runs 1 -
the met
as repr

Analyses of Make Gases

The gas generator operates continuously and for the plant record, the gross heating value of the gas is determined by a Thomas recording calorimeter, the specific gravity by a Renorex meter, and the CO_2 by a Republic meter. These instruments indicate constant conditions throughout a balanced period. It was not feasible to collect and store samples of the gases made over the entire 24-hour testing period because of limitations in technical personnel and suitable storage equipment. Representative samples of the gases made were therefore collected during 1- to 4-hour periods, and the analyses of these were considered representative of the entire testing period when static operating conditions were attained.

At Golden, samples of make gas were introduced in a 20-cubic-foot gas holder at a constant rate and stored over water. The gas entering the holder was sampled every 10 minutes for determination of CO_2 content, as some absorption of CO_2 took place in the water-sealed gas holder. The sample for complete gas analysis and for additional tests in the plant instruments was withdrawn from the holder, and corrections were made for any CO_2 absorption.

At Grand Forks, samples of make gas were stored over brine solution in a small sampling system, which received a steady supply of gas from the main gas line leaving the plant exhauster. The CO_2 in the gas was determined at intervals. The sample thus obtained was suitable for gas analysis but insufficient for tests in the plant instruments. This method of sampling was employed for all samples reported up to run 4. Another method of sampling was used for run 4 at Grand Forks, which avoided some of the troubles and manipulative errors encountered with the first sampling system. A stream of gas flowing at a rate of 3 to 5 cubic feet per hour was introduced in a 20-cubic foot receiver. The gas emerging from the receiver was considered a mixture of gases entering for several hours previous to the time of taking the sample. When passing gas through the 20-cubic foot receiver at a rate of 4 cubic feet per hour, the gas emerging can be considered to represent approximately 5 hours of operation. This method of sampling into a large dry receiver eliminated the errors in CO_2 absorption, and it was much simpler than sampling gases into a small receiver employing a confining solution, which absorbed even slight amounts of CO_2 .

Table 15 gives the analyses of gases produced during runs 10, 11, and 12 in the small pilot plant, and table 16 gives similar analyses of gases for runs 1 to 4 in the large pilot plant. The footnotes to these tables explain the methods of sampling, and they designate the particular samples reported as representative of the testing period.

R. I. 4128

TABLE 15. - Analyses of make gases, runs 10, 11, and 12, Golden pilot plant, 1945.

Run and period	Date	Time/	Analysis, percent						Sulfur grains per Ccf		Specific gravity (air - 1.0)	B.t.u. per cu. ft.		Remarks	
			CO ₂	H ₂	CH ₄	C ₂ H ₆	N ₂	H ₂ S	Organic	Thomas gross		Calc. gross	Calc. net		
10-A	8-7	10:50A75	10.8	29.3	56.4	3.3	0.0	0.0	0.064	0.551	0.508	313	310	278	3/4/
10-B	8-8	7:50A90	12.0	28.1	56.2	3.2	.0	.1	3.33	.581	.518	315	308	277	2/4/
11-A	9-19	8:45A95	13.0	26.2	56.2	3.7	.0	.5	2.46	.558	.522	300	307	275	3/4/
12-A	11-6	8:20P305	13.5	24.9	56.3	4.4	.0	.5	2.32	.557	.520	314	310	278	3/5/
12-A	11-7	8:30A85	10.0	30.3	54.8	4.0	.0	.5	.499	.547	.516	320	318	287	4/
12-B	11-7	4:30P240	13.3	26.2	56.6	3.2	.0	.5	3.00	.551	.521	302	299	268	2/5/
12-B	11-8	9:00A90	12.9	26.5	56.4	3.3	.0	.5	3.11	.550	.520	304	305	273	4/
12-C	11-9	9:30A85	13.6	26.2	55.3	4.0	.0	.5	2.70	.582	.531	309	307	275	3/4/

1/ Samples for analyses were taken at a constant rate, beginning at the time indicated and continuing for the given number of minutes. For example, during period 10-A, designated thus - 10:50A75, the sampling was started at 10:50 A.M. and continued for 75 minutes.

2/ Illuminants are assumed to have the average composition of C₂H₅.6. The composition was estimated from heat and material balances of several tests on the small and the large pilot plants.

3/ This analysis is reported as representing the entire testing period.

4/ Sample for analysis was taken at a constant rate into a 20 cu. ft. water-sealed holder. The average CO₂ in the gas was determined before it entered the holder, and the complete analysis was corrected to this CO₂ basis. The H₂S and organic sulfur determinations were made on the gas taken from the holder.

5/ Sample for analysis was taken at a constant rate from the line directly after the scrubber system into a container over a confining solution of saturated brine. The average CO₂ in the gas was determined before it entered the container, and the complete analysis was corrected to this CO₂ basis. The H₂S and organic sulfur determinations were made on the gas from the same source.

R. I. 4128

TABLE 16. - Analyses of make gases, run 1, Grand Forks pilot plant, June 1945.

Run and period	Date	Time/	Analysis, percent							Sulfur grains per Ccf	Specific gravity (air = 1.0)	B.t.u. per cu. ft.		Remarks
			Analysis, percent									Thomas gross	Calc. net	
			CO ₂	H ₂	CH ₄	C ₂ H ₆	N ₂	H ₂ S	Organic					
1-A	18	9:05A85	22.3	56.2	5.0	0.0	2.0			0.560	275	282	248	P
1-A	18	1:00P120	22.4	57.2	5.1	0	.5			.572	280	287	252	G
1-A	19	10:00A110	22.1	54.1	3.5	.9	4.2			.590	277	278	245	P
1-B	19	7:45P120	22.4	56.6	3.7	.9	.5			.570	289	290	256	G 4/
1-B	19	9:45P35	22.5	56.7	4.6	0	.6			.580	278	278	244	P
1-B	19	9:45P120	22.4	56.9	4.6	0	.5			.579	278	278	245	G
1-B	19	9:45P35	23.5	58.4	5.1	0	1.7			.554	273	276	242	P
1-B	20	9:20A115	23.6	59.2	5.2	0	.5			.548	281	280	246	G 2/
1-B	20	8:45A105	23.5	57.4	4.8	0	.3			.595	270	280	247	P
1-B	20	7:25P70	24.0	55.2	3.1	.6	3.3			.580	273	265	233	G
1-C	22	7:25P70	24.7	54.2	5.1	1.1	1.9			.589	280	270	238	P
1-C	22	7:25P70	24.5	54.9	4.5	.3	.2			.590	281	282	249	G 2/
1-C	23	3:20P120	22.4	58.3	3.3	.6	2.1			.592	286	288	255	G 6/
1-C	23	3:20P120	22.7	59.3	3.4	.6	.5			.585	282	281	249	P
1-C	23	3:20P120	22.7	59.3	3.4	.6	.5			.580	275	277	243	G
1-C	23	3:20P120	22.7	59.3	3.4	.6	.5			.592	279	281	247	G 4/

TABLE 16. - Analyses of make gases, run 2, Grand Forks pilot plant, December 1945.

2-A	9	1:40P25	17.4	59.6	3.0	0.0	0.1	0.440	0.966	0.519	297	288	255	4/1/
2-B	10	3:00P90	15.7	56.4	3.3	0	.8	.292	1.35	.541	296	295	265	4/1/
2-C	12	9:50A85	14.0	56.4	2.9	0	.1	.470	1.01	.523	303	300	268	4/1/
2-D	13	12:45P95	15.8	55.6	4.4	0	.4			.538	309	308	275	4/
2-E	15	3:30P90	15.6	56.7	3.9	0	.1	.769	1.54	.536	308	308	275	4/1/

See footnotes on page 48.

TABLE 16. - Analyses of make gases, run 3, Grand Forks pilot plant, March 1946. (cont'd.)

Run and period	Date	Time/	Analysis, percent							Sulfur		Specific gravity (air = 1.0)	B. t. u. per cu. ft.		Remarks	
			CO ₂	H ₂	CH ₄	C ₂ H ₆	N ₂	H ₂ S	Organic	Thomas gross	Calc. gross		Calc. net			
3-A	9	8:30P60	25.3	10.7	59.7	2.6	1.0	0.4				0.559	274	274	240	
3-A	10	9:20A60	25.2	10.9	59.2	3.3	.4	.6			0.216	1.32	271	271	238	4/7/
3-B	14	1:00P60	17.3	21.1	57.2	3.8	.0	.0				.539	300	299	266	4/7/
3-BC	15	3:00P90	17.4	21.7	56.2	3.7	.3	.1			.066	2.50	288	302	269	4/7/
3-C	16	12:35P165	18.6	20.0	57.7	3.2	.2	.0			.105	1.90	288	289	256	4/7/
3-D	16	7:00P150	18.6	20.0	57.2	3.4	.1	.3					288	289	257	
3-D	17	12:30A195	19.1	18.1	58.2	3.7	.0	.5					287	288	255	
3-D	17	3:00P90	18.5	20.1	57.1	3.1	.3	.7			.158	2.44	287	286	254	4/7/
3-F	18	6:00P260	16.9	22.4	56.2	4.2	.0	.1			.700	5.47	297	296	264	8/4/
3-F	19	1:45P90	16.5	22.7	55.9	4.1	.0	.6					297	295	263	
3-FG	20	10:35P85	14.4	25.5	55.7	3.3	.0	.9					298	296	264	
3-G	21	10:45A60	14.3	25.4	55.4	3.5	.1	1.0			.807	8.51	298	300	268	4/8/
3-CH	22	1:45P105	16.0	23.0	55.9	3.2	.5	1.1					297	298	266	
3-H	23	1:00A270	16.0	22.7	55.7	3.9	.0	1.3					295	297	265	
3-H	23	2:00P60	16.0	23.0	55.7	4.1	.0	.8			.680	8.95	297	299	267	4/8/
3-J	24	1:00A240	15.5	24.2	55.1	4.2	.0	.6			.585	8.15	299	302	270	8/

See footnotes on page 48.

TABLE 16. - Analyses of make gases, run 4, Grand Forks pilot plant, April-May 1946. (cont'd.)

TABLE 16. - Analyses of make gases, run 4, Grand Forks pilot plant, April-May 1946. (cont'd.)

Run and period	Date	Time	Analysis, percent					Specific gravity (air = 1.0)		B.t.u. per cu. ft.		Remarks		
			CO ₂	CO	H ₂	CH ₄	C ₂ H ₆	N ₂	Kanarex	Calc.	Thomas gross		Calc. gross	Calc. net
4-A	17	10:00A	15.9	0.3	22.1	58.9	1.3	0.6	0.9	0.538	265	287	256	4/
4-B	19	8:30A120	17.8	.3	22.1	56.4	2.8	.4	.2	.545	290	291	260	4/
4-C	19	8:00A	18.2	.4	22.7	55.3	3.3	.0	.1	.545	290	290	259	4/
4-D	21	1:15P	17.4	.3	20.8	58.5	2.0	.6	.4	.543	292	289	257	4/
4-E	21	8:10A140	17.6	.3	20.7	58.7	2.0	.6	.1	.543	292	290	257	4/
4-F	23	6:00P	16.9	.3	19.9	59.6	3.0	.2	.1	.540	294	292	225	4/
4-G	23	8:20P130	18.1	0.3	20.0	59.3	1.9	0.2	0.2	.542	292	282	250	4/
4-H	25	10:00A	17.7	.3	21.2	58.4	1.7	.4	.3	.540	292	284	252	4/
4-I	25	7:30P5	17.6	.3	20.7	58.8	2.0	.2	.4	.540	296	282	250	4/
4-J	27	6:00P	16.4	.4	20.1	60.2	1.7	.7	.5	.536	294	293	260	4/
4-K	28	9:45P	16.3	.3	20.8	59.0	2.5	.6	.5	.530	293	296	263	4/
4-L	28	8:45A130	16.1	.3	22.6	58.8	1.4	.2	.6	.530	293	283	252	4/
4-M	29	1:35P	17.0	0.4	20.2	59.6	1.9	0.4	0.5	.540	291	289	256	4/
4-N	30	2:30P135	16.7	.2	21.6	59.3	1.6	.3	.3	.535	294	283	252	4/
4-O	1	8:10P	18.0	.4	20.8	57.9	1.9	.6	.4	.540	291	289	257	4/
4-P	2	4:20P	18.0	.3	19.4	59.3	2.2	.4	.4	.540	294	286	254	4/
4-Q	2	2:45P115	18.0	.3	19.1	59.7	2.0	.4	.5	.540	294	286	253	4/
4-R	3	3:05P	16.2	.3	22.5	57.0	3.1	.7	.2	.538	296	303	270	4/
4-S	4	2:45P135	15.8	0.4	23.0	56.8	2.2	1.2	0.6	.535	293	306	273	4/
4-T	4	5:30P	15.9	.4	22.5	56.6	3.1	1.0	.5	.535	293	309	276	4/
4-U	5	2:15P	17.0	.3	21.4	57.4	2.6	.9	.4	.535	290	299	266	4/
4-V	6	2:35P150	17.0	.3	21.4	58.1	2.5	.3	.4	.535	290	290	258	4/
4-W	6	2:00P	17.0	.4	20.4	59.8	1.8	.2	.4	.535	290	286	253	4/
4-X	7	4:40P	15.6	.2	23.8	57.5	2.2	.2	.5	.540	292	289	257	4/

See footnotes on page 48.

TABLE 16. - Analyses of make gases, run 4, Grand Forks pilot plant, April-May 1946. (cont'd.)

Run and period	Date	Time	Analysis, percent						Specific gravity (air = 1.0)	B. t. u. per cu. ft.		Remarks		
			CO ₂	CO	H ₂	CH ₄	C ₂ H ₆	N ₂		Thomas gross	Calc. gross		Calc. net	
4-K	8	2:42P150	15.0	0.2	23.7	58.6	1.8	0.3	0.4	0.540	292	288	237	4/
4-K	8	5:05P	15.4	.2	23.9	58.1	1.7	.2	.5	.540	292	286	255	4/
4-KL	9	1:20P	17.3	.3	21.8	57.3	2.5	.3	.5	.540	291	289	237	4/
4-L	10	3:45P	17.1	.3	21.9	57.4	2.6	.2	.5	.540	291	288	237	4/
4-L	10	2:30P130	17.0	.3	21.9	57.6	2.5	.2	.5	.540	291	288	256	4/
4-LM	11	1:30P	18.6	.3	20.3	58.2	2.1	.2	.3	.540	286	281	249	4/
4-M	12	7:45A130	18.7	0.2	19.5	58.3	2.5	0.3	0.5	.542	285	282	250	4/
4-M	12	7:50A	18.7	.4	19.4	59.2	1.7	.2	.4	.542	285	279	247	4/
4-N	13	4:20P	19.2	.3	19.0	58.6	2.4	.1	.4	.541	285	279	247	4/
4-N	13	3:15P155	19.1	.2	18.8	58.7	2.5	.2	.5	.541	285	280	248	4/
4-NO	15	8:00A	17.3	.0	22.6	58.9	.8	.0	.4	.533	252	268	238	4/
4-O	15	10:00A	15.8	.2	23.2	58.7	1.6	.0	.5	.542	268	271	240	4/
4-O	15	10:50A120	16.8	.0	22.9	59.1	.8	.0	.4	.542	268	270	239	4/
4-O	15	9:00P75	15.0	.1	24.2	59.1	1.2	.1	.3	.542	268	271	241	4/

1/ Samples for analyses were taken in a container over a confining solution of saturated brine at a constant rate beginning at the time indicated and continuing for the given number of minutes. For example, during period 1-A, designated as 9:05A85, the sampling was started at 9:05 A.M. and continued for 85 minutes. Those samples with only an initial time given are grab samples taken direction into the gas analysis apparatus from the outlet of a 20 cu. ft. dry vessel, through which gas circulated at approximately 5 cu. ft. per hour. Such a sample represents the probable average of the gas for 4 hours prior to the time the sample was taken. The latter method avoids the absorption of CO₂ in the confining solution.

2/ Illuminants are assumed to have the average composition of C₂H₅.6. The composition was estimated from heat and material balances of several tests on the small and the large pilot plants.

3/ During run 1, purge gas containing 17 percent CO₂ and 83 percent N₂ was introduced in the top and bottom of the generator to reduce moisture condensation and to avoid explosive mixtures in the charging hopper.

Corrections were made for this dilution of the generator gas, the composition of which was calculated, assuming it to contain only 0.5 percent nitrogen. F designates the plant gas containing purge gas; G designates the calculated generator gas. In the subsequent runs, purge gas introduced was insignificant. This analysis is reported as representing the entire testing period.

4/ Average of these reported as representing the testing period 1-B.

5/ This analysis represents a change-over period between B and C.

6/ Gas samples for H₂S and organic sulfur determinations were taken from line to laboratory.

7/ Gas samples for H₂S and organic sulfur determinations were taken at gas off-take before passing through the water scrubber.