

GASIFICATION OF LIGNITE IN A COMMERCIAL-SCALE PILOT PLANT:
PROGRESS REPORT JANUARY 1, 1949 TO JUNE 30, 1950

by

A. C. Burr,^{1/} R. C. Ellman,^{2/} J. J. Hoeppner,^{3/} J. C. Holtz,^{4/} T. W. Kamps,^{5/}
W. R. Kube,^{5/} O. C. Ongstad,^{6/} and W. H. Oppelt^{7/}

CONTENTS

	<u>Page</u>
Summary abstract	1
Introduction	2
Acknowledgments	2
Objectives of gasification experiments	3
General objectives	3
Specific objectives	3
Description of commercial-scale pilot plant	4
General	4
Flow diagram and description of operation	4
Retort unit	4
Auxiliary equipment	5
Instrumentation, methods of testing and obtaining data, accuracy of results	6
Test runs, operating conditions, and lignite gasified	7
Run 10	7
Run 11	8
Run 12	10
Run 13	12
Results and discussion of tests	15
General	15
Run 10	15
Run 11	16
Run 12	19
Run 13	26

-
- ^{1/} Formerly chief, Fuels Technology Division, Region V, now
consultant, Bureau of Mines, Grand Forks, N. Dak.
^{2/} Chief, Preparation Section, Bureau of Mines, Grand Forks, N. Dak.
^{3/} Chemist, Bureau of Mines, Grand Forks, N. Dak.
^{4/} Formerly chief, Chemistry and Physics Section, Bureau of Mines,
Grand Forks, N. Dak.
^{5/} Chemical engineer, Bureau of Mines, Grand Forks, N. Dak.
^{6/} Formerly chemical engineer, Bureau of Mines, Grand Forks, N. Dak.
^{7/} Chief, Utilization Section, Bureau of Mines, Grand Forks, N. Dak.

CONTENTS (Cont.)

	<u>Page</u>
Material and heat balances	29
Behavior of retort tubes	31
Influence of mass velocity of gas and water vapors leaving gas offtake on behavior of gas generator	33
Distribution of sulfur during gasification of lignite	35
Summary and conclusions	38
Bibliography	41
Appendix	41

TABLES

1. Typical analyses of natural Dakota Star lignite as charged during run 11	9
2. Size consist of natural Dakota Star lignite as charged during run 11	10
3. Summary of experimental conditions for run 12	11
4. Typical analyses of steam-dried Dakota Star lignite as gasified during run 12	12
5. Size consist of steam-dried Dakota Star lignite as charged during run 12	12
6. Experimental conditions for run 13	14
7. Typical analyses of natural Dakota Star lignite as gasi- fied during run 13	15
8. Size consist of natural Dakota Star lignite as charged during run 13	15
9. Analyses of residue from the gasification process at various percentages of carbon gasified during run 11 ...	18
10. Size consist of residue at various percentages of carbon gasified during run 11	19
11. Comparison of gasification of natural and steam-dried lig- nite at various H ₂ -CO ratios	20
12. Influence of size consist of steam-dried lignite on gasi- fication process	23
13. Analyses of residue from gasification process at various percentages of carbon gasified, during run 12	24
14. Size consist of residue at various percentages of carbon gasified during run 12	25
15. Analyses of residue from gasification process at various percentages of carbon gasified during run 13	28
16. Size consist of residue at various percentages of carbon gasified during run 13	29
17. Summary of operation of commercial-scale pilot plant, February 1945 to July 1950	32
18. Typical concentration of sulfur in product gas during runs 11 through 13	36
19. Summary of sulfur balances for run 13	37
20. Composition of special char samples collected during run 13	37
21. Weight of ash deposits collected from inner wall of 310- alloy tube	38

TABLES (Cont.)

	<u>Page</u>
22. Summary data on gasification of natural and dried lignite, runs 11 through 13	42
23. Experimental data and calculations converted to moisture- and ash-free basis for runs 11 through 13	45
24. Material balances for runs 11 through 13	46
25. Heat balances for runs 11 through 13	47

ILLUSTRATIONS

<u>Fig.</u>	<u>Follows page</u>
1. Plan view of Government property and lignite-gasification unit, Grand Forks, N. Dak.	4
2. Aerial view of Government property on University of North Dakota campus	4
3. Flow diagram of Grand Forks lignite-gasification process, showing divided annulus arrangement of retort ...	4
4. Arrangement of retort unit for runs 10, 11, 12, and 13 .	4
5. Steam chest being lowered into retort	4
6. Packing gland seal connecting retort tube to char-disposal unit	4
7. Recuperator tube nest constructed from 23-12 stainless steel	6
8. Influence of lignite feed rate on performance of gas generator; H ₂ -CO ratio 2.30:3.04	16
9. Influence of lignite feed rate on performance of gas generator; H ₂ -CO ratio 3.38:3.99	16
10. Influence of lignite feed rate on performance of gas generator; H ₂ -CO ratio 4.40:4.84	16
11. Performance of the gas generator as a function of the lignite feed rate, run 11	16
12. Percentage carbon gasified as a function of the inner tube temperature	16
13. Gas yield per ton of moisture- and ash-free lignite as a function of total water available and location of steam admission	26
14. Distribution of product gas as a function of total water available and location of steam admission	26
15. Percentage of carbon gasified as a function of total water available and location of steam admission	26
16. H ₂ -CO ratio of product gas as a function of total water available and location of steam admission	26
17. Material entering and leaving annulus during gasification process	30
18. Heat distribution during gasification at various hydrogen-carbon monoxide ratios of product gas	30

ILLUSTRATIONS (Cont.)

Fig.		Follows page
19.	Radial dimensions of HK alloy retort tube as received .	30
20.	Exterior and interior views of broken weld of HK cast- alloy tube	30
21.	Cross sections of broken weld of HK cast-alloy tube ...	32
22.	310-alloy tube being lowered into the retort for first test	32
23.	Corrosion of inner surface of 310-alloy tube before and after run 13	32
24.	310-alloy plate retort tube: Variation in length of radii	32
25.	Product-gas recorder chart for period 11-MN, showing fluctuations in gas production	34
26.	Weight of blow-over dust as a function of mass velocity of gas and steam leaving gas offtake	34
27.	Size consist of blow-over dust as a function of mass velocity of gas and steam leaving gas offtake	34
28.	Percentage of total sulfur in charge transferred to product gas as a function of unreacted steam	36
29.	Percentage of total sulfur in charge transferred to product gas as a function of unreacted steam and location of steam admission	36