

EXPERIMENTAL AND COMPUTATIONAL STUDIES OF
HYDRODYNAMICS IN THREE-PHASE AND TWO-PHASE FLUIDIZED BEDS

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

BY

MITRA BAHARY

Submitted in partial fulfillment of the
requirements for the degree of
Doctor of Philosophy in Chemical Engineering
in the Graduate School of the
Illinois Institute of Technology

Approved *Dimitri Gidopoulos*
Advisor

Chicago, Illinois
December 1994

MASTER

LW

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

ACKNOWLEDGEMENT

First and foremost, I would like to thank God, the most beneficent, and the most merciful.

I would like to express my sincere appreciation and gratitude to my thesis advisor, Professor Dimitri Gidaspow, for his guidance and encouragement, and providing me with financial support during the course of this work.

Sincere thanks are due to my colleagues, especially Dr. Umesh K. Jayaswal, with whom I had many useful discussions. Help rendered by my other colleagues, Dr. Aubrey L. Miller, Dr. Isaac K. Gamwo, Dr. Apichai Therdihianwong, Ms. Bing Sun , Mr. Yuanxiang Wu, and Mr. Lu Huilin is sincerely appreciated.

Finally and most importantly, I come to my family. My greatest appreciation goes to my Father, my mother and my brothers. They were a constant source of support, encouragement and inspiration. Without their patience, understanding and sacrifices, this study would have never been possible.

Furthermore, my thanks are extended to the staff of Chemical Engineering Departement in IIT.

Financial support for this study was provided by the grants from the Department of Energy grant No. DOE DEFG 22-94PC94208, National Science Foundation grant No. CTS-9305850, and AMOCO Corporation.

M.B

TABLE OF CONTENTS

	Page
ACKNOWLEDGEMENT	iii
LIST OF TABLES	vii
LIST OF FIGURES	ix
LIST OF SYMBOLS	x
ABSTRACT	xiii
 CHAPTER	
I. INTRODUCTION	1.1
II. DESCRIPTION OF EXPERIMENTAL APPARATUS FOR THREE-PHASE FLUIDIZED BED	2.1
Introduction	2.1
Experimental Apparatus and Procedure	2.2
Visual Observations of Bubble Coalescence and Break up ..	2.7
III. MEASUREMENTS OF VOLUME FRACTIONS IN TWO-PHASE AND THREE-PHASE FLUIDIZED BEDS	3.1
Introduction	3.1
Principle of Interpretation	3.1
Calibration of X-ray and γ -ray Densitometer	3.3
Flow Regime	3.4
Volume Fractions	3.5
IV. POWER SPECTRA ANALYSIS OF BUBBLE FREQUENCY	4.1
Introduction	4.1
Experimental Setup and Procedure	4.3
Experimental Concentration Fluctuation and Power Spectra	
Results	4.4
Computed Concentration Fluctuation and Power Spectra	
Results	4.21
Conclusion	4.21

CHAPTER	Page
V. PARTICLE VELOCITY DISTRIBUTION IN TWO-PHASE AND THREE-PHASE FLUIDIZED BED	5.1
Introduction	5.1
Apparatus and Experimental Procedure	5.2
Analysis of Results	5.8
Conclusion	5.23
VI. SOLIDS VISCOSITY MEASUREMENTS IN THREE-PHASE FLUIDIZED BED	6.1
Introduction	6.1
Experimental Setup and Procedure	6.3
"Apparent" Bed Viscosity	6.6
Shear Stress Analysis	6.13
Granular Temperatures in Three-Phase Fluidized Beds	6.14
Conclusion	6.17
VII. DESCRIPTION OF THE HYDRODYNAMIC MODEL AND SIMULATION	7.1
Introduction	7.1
Hydrodynamic Model	7.2
Numerical Scheme	7.3
Initial and Boundary Conditions	7.4
Fluidized Bed Simulation	7.6
Results of Numerical Simulation	7.6
Conclusion	7.19
VIII. SUMMARY AND RECOMMENDATIONS	8.1
Summary	8.1
Future Work	8.2

	Page
A. VOLUME FRACTION MEASUREMENT DATA	A.1
B. VELOCITY MEASUREMENT DATA	B.1
C. VISCOSITY MEASUREMENT DATA	C.1
D. HYDRODYNAMIC MODEL	D.1
REFERENCES	R.1

LIST OF TABLES

Table	Page
2.1 Experimental Operating Conditions	2.7
4.1 Bubble Frequencies in Three-Phase Fluidized Bed at Different Locations	4.20
6.1 "Apparent" Bed Viscosity	6.10
A-1. Experimental Data for Volume Fractions in Air-Water-Glass Beads Fluidized Bed (Superficial Gas Velocity = 3.36 cm/s, Superficial Liquid Velocity = 2.0 cm/s)	A.2
B-1. Raw Solids Velocity Data for Liquid-Solid Fluidized Bed with Uniform Distributor at X= 4.0 cm and Y= 4.5 cm (Superficial Liquid Velocity = 4.0 cm/sec)	B.2
B-2. Statistical Analysis on Solids Velocities Data in Table B-1	B.7
B-3. Frequency Distribution for Axial Solids Velocity from Table B-1	B.8
B-4. Frequency Distribution for Radial Solids Velocity from Table B-1	B.9
B-5. Raw Solids Velocity Data for Liquid-Solid Fluidized Bed with Uniform Distributor at X= 4.0 cm and Y= 4.5 cm (Superficial Liquid Velocity = 6.0 cm/sec)	B.10
B-6. Statistical Analysis on Solids Velocities Data in Table B-5	B.15
B-7. Frequency Distribution for Axial Solids Velocity from Table B-5	B.16
B-8. Frequency Distribution for Radial Solids Velocity from Table B-5	B.17

Table	Page
B-9. Raw Solids Velocity Data for Gas-Liquid-Solid Fluidized Bed with Uniform Distributor at X= 4.0 cm and Y= 4.5 cm (Superficial Liquid Velocity = 6.0 cm/sec, Superficial Gas Velocity = 3.36 cm/sec)	B.18
B-10. Raw Solids Velocity Data for Gas-Liquid-Solid Fluidized Bed with Uniform Distributor at X= 7.5 cm and Y= 9.0 cm (Superficial Liquid Velocity = 4.0 cm/sec, Superficial Gas Velocity = 3.36 cm/sec)	B.22
B-11. Raw Solids Velocity Data for Gas-Liquid-Solid Fluidized Bed with Uniform Distributor at X= 7.5 cm and Y= 9.0 cm (Superficial Liquid Velocity = 7.23 cm/sec, Superficial Gas Velocity = 3.36 cm/sec)	B.27
B-12. Raw Solids Velocity Data for Gas-Liquid-Solid Fluidized Bed with Central Jet Distributor at X = 23.0 cm and Y = 10.0 cm (Inlet Liquid Velocity = 439.52 cm/sec, Inlet Gas Velocity = 578.88 cm/sec, Inlet Gas Velocity of Left Gas Inlet = 370 cm/sec, Inlet Gas Velocity of Right Gas Inlet = 243 cm/sec)	B.33
C-1. Raw Viscosity Data at different Spindle Rotation Rate for Three-Phase Fluidized Bed with Uniform Distributor (Superficial Liquid Velocity = 2.037 cm/sec, Superficial Gas Velocity = 3.364 cm/sec, Particles Diameter of 0.08 mm)	C.2
C-2. Raw Viscosity Data at Spindle Rotation Rate of 6 rpm for Three-Phase Fluidized Bed with Central Jet Distributor at different Inlet Liquid Velocities (Inlet Gas Velocity at Right Inlet = 131.0 cm/sec, Inlet Gas Velocity at Left Inlet = 135.0 cm/sec, Particles Diameter = 1.0 mm)	C.6
C-3. Raw Viscosity Data at Spindle Angular Velocity of 6 rpm for Liquid-Solid Fluidized Bed with Central Jet Distributer (Particles Diameter = 1.0 mm)	C.15

Table

Page

D-1. Governing Equations -- Hydrodynamic Model B for Gas-Liquid-Solid Flow D.2

LIST OF FIGURES

Figure	Page
2.1. Schematic Diagram of the Experimental Apparatus	2.3
2.2. Schematic Diagram of Source-Detector-Recorder Assembly for X-ray and G-ray Densitometer	2.5
2.3. Mechanism of Coalescence and Disintegration of Bubbles in Gas- Liquid-Solid Fluidized Beds (Fan, 1989)	2.9
3.1. An X-Ray Calibration Curve for Lead Glass Beads	3.7
3.2. An g-Ray Calibration Curve for Lead Glass Beads	3.8
3.3. Flow Regime Map for a Liquid-batch Bubble Column or a Slurry-batch Slurry Bubble Column Containing a Low Viscosity Liquid Phase (from Deckwer et al. 1980)	3.9
3.4. Photograph of Coalescence Regime in a Gas-Liquid-Solid Fluidized Bed, with Uniform Liquid and Gas Injection	3.10
3.5. Flow Regime Diagram for Cocurrent Gas-Liquid-Solid Fluidized Beds (from Muroyama and Fan, 1985)	3.11
3.6. The Portion of The Bed Where Measurements Were Obtained	3.12
3.7(a). Experimental Time Average Volume Fraction Contours for Liquid	3.13
3.7(b). Experimental Time Average Volume Fraction Contours for Gas	3.14
3.7(c). Experimental Time Average Volume Fraction Contours for Solid	3.15

Figure	Page
4.1. Schematic Diagram of Porosity Acquisition System (Gamwo, 1992)	4.2
4.2. Experimental Measurement of Fluctuation of Bubble at X=15.24 cm and Y=3.81 cm for Gas-Liquid-Solid System	4.5
4.3. Approximated Porosity Power Spectrum at X=15.24 cm and Y=3.81 cm for Gas-Liquid-Solid System	4.6
4.4. Experimental Measurement of Fluctuation of Bubble at X=10.16 cm and Y=12.7 cm for Gas-Liquid-Solid System	4.7
4.5. Approximated Porosity Power Spectrum at X=10.16 cm and Y=12.7 cm for Gas-Liquid-Solid System	4.8
4.6. Experimental Measurement of Fluctuation of Bubble at X=12.70 cm and Y=12.7 cm for Gas-Liquid-Solid System	4.11
4.7. Approximated Porosity Power Spectrum at X=12.70 cm and Y=12.7 cm for Gas-Liquid-Solid System	4.12
4.8. Experimental Measurement of Fluctuation of Bubble at X=15.28 cm and Y=3.81 cm for Gas-Liquid System	4.13
4.9. Porosity Power Spectrum at X=15.28 cm and Y=3.81 cm for Gas-Liquid System	4.14
4.10. Experimental Measurement of Fluctuation of Bubble at X=10.16 cm and Y=12.7 cm for Gas-Liquid System	4.15
4.11. Porosity Power Spectrum at X=10.16 cm and Y=12.70 cm for Gas-Liquid System	4.16
4.12. Experimental Measurement of Fluctuation of Bubble at X=12.7 cm and Y=12.7 cm for Gas-Liquid System	4.17

Figure	Page
4.13. Porosity Power Spectrum at X=12.70 cm and Y=12.70 cm for Gas-Liquid System	4.18
4.14. Bubble Frequencies along the Bubble Path	4.19
4.15. Computational Data of Fluctuation of Bubble at X=15.28 cm and Y=4 cm for Gas-Liquid-Solid System	4.22
4.16. Porosity Power Spectrum at X=15.24 cm and Y=4 cm for Gas-Liquid-Solid System	4.23
4.17. Computational Data of Fluctuation of Bubble at X=10.16 cm and Y=12 cm for Gas-Liquid-Solid System	4.24
4.18. Porosity Power Spectrum at X=10.16 cm and Y=12 cm for Gas-Liquid-Solid System	4.25
4.19. Computational data of Fluctuation of Bubble at X=13.20 cm and Y=12 cm for Gas-Liquid-Solid System	4.26
4.20. Porosity Power Spectrum at X=13.20 cm and Y=12 cm for Gas-Liquid-Solid System	4.27
5.1. Schematic Diagram of Experimental Apparatus of Fluidized Bed W/uniform Distributor	5.5
5.2. Schematic Diagram of Experimental Apparatus of Fluidized Bed W/central Jet Distributor	5.6
5.3. The Image Captured by the Recording System	5.7
5.4. Distribution of Mean Solid Speed at X=4 cm and Y=4.5 cm for Liquid-Solid System with $V_f=4$ cm/sec	5.9

Figure	Page
5.5. Distribution of Axial Velocity of Particles at X=4 cm and Y=4.5 cm for Liquid-Solid System with $V_f=4$ cm/sec	5.10
5.6. Distribution of Radial Velocity of Particles at X=4 cm and Y=4.5 cm for Liquid-Solid System with $V_f=4$ cm/sec	5.11
5.7. Distribution of Mean Solid Speed at X=4 cm and Y=4.5 cm for Liquid-Solid System with $V_f=4$ cm/sec	5.12
5.8. Velocity Distribution of Particles (Carlos, and Richardson, 1968)	5.15
5.9. Solids Granular Temperature as Function of Liquid Velocity at X=4 cm, and Y=4.5 cm	5.16
5.10. Solids Viscosity As Function of Liquid Velocity in Liquid-Solid Fluidized Bed	5.17
5.11. Distribution of Mean Solid Speed at X=4 cm and Y=4.5 cm for Liquid-Solid-Gas System with $V_f=4$ cm/sec and $V_g=3.36$ cm/sec	5.18
5.12. Distribution of Axial Velocity of Particles at X=4 cm and Y=4.5 cm for Liquid-Solid-Gas System with $V_f=4$ cm/sec and $V_g=3.36$ cm/sec	5.19
5.13. Distribution of Radial Velocity of Particles at X=4 cm and Y=4.5 cm for Liquid-Solid-Gas System with $V_f=4$ cm/sec and $V_g=3.36$ cm/sec	5.20
5.14. Distribution of Mean Solid Speed at X=7.5 cm and Y=9.0 cm for Liquid-Solid-Gas System with $V_f=4$ cm/sec and $V_g=3.36$ cm/sec	5.21
5.15. Distribution of Mean Solid Speed at X=7.5 cm and Y=9.0 cm for Liquid-Solid-Gas System with $V_f=7.23$ cm/sec and $V_g=3.36$ cm/sec	5.22

Figure	Page
5.16. Experimental Velocity Profile as Function of Radial Distance in Liquid-Solid-Gas System with $V_f=3.7$ cm/sec and $V_g=7.45$ cm/sec	5.25
5.17. Solid Granular Temperature Vs. Radial Distance	5.26
5.18. Solid Granular Temperature Vs. Radial Distance	5.27
5.19. Solid Granular Temperature Vs. Radial Distance	5.28
5.20. Distribution of Mean Solid Speed at X=23 cm and Y=10 cm for Liquid-Solid-Gas System with $V_f=439$ cm/sec and $V_{g1}=243$ cm/sec $V_{g2}=578$ cm/sec $V_{g3}=370$ cm/sec	5.29
5.21. Distribution of Axial Velocity of Particles at X=23 cm and Y=10 cm for Liquid-Solid-Gas System with $V_f=439$ cm/sec and $V_{g1}=243$ cm/sec $V_{g2}=578$ cm/sec $V_{g3}=370$ cm/sec	5.30
5.22. Distribution of Radial Velocity of Particles at X=23 cm and Y=10 cm for Liquid-Solid-Gas System with $V_f=439$ cm/sec and $V_{g1}=243$ cm/sec $V_{g2}=578$ cm/sec $V_{g3}=370$ cm/sec	5.31
5.23. Solid Viscosity as Function of Liquid Velocity in Liquid-Solid-Gas Fluidized Bed with Central Jet Distributer	5.32
6.1. Schematic Diagram of the Experimental Apparatus	6.4
6.2. Experimentally Measured Viscosity (cp) Versus Spindle Rotation Rate for Three Phase Fluidized Bed (solid Dia =800 micron, Sup Gas Velo. = 3.36 cm/sec)	6.7
6.3. Experimentally Measured Viscosity Vs. Shear Rate	6.8

Figure	Page
6.4. Experimentally Measured Viscosity Vs. Numbers of Run for Spindle Rotation Rate of 6 rpm for Three-Phase Fluidized Bed with Central Jet (Solid Dia. = 0.08 mm)	6.11
6.5. Experimentally Measured Viscosity Vs. Numbers of Run for Spindle Rotation Rate of 6 rpm for Three-Phase Fluidized Bed with Central Jet (Solid Dia.=1 mm)	6.12
6.6. Experimentally Measured Shear Stress Vs. Velocity Gradient for Three-Phase Fluidized Bed (Solid Dia. = 0.08 mm, Sup. Gas Velo. = 3.364 cm/sec)	6.15
6.7. Experimentally Measured Shear Stress Vs. Velocity Gradient for Two-Phase Fluidized Bed (Solid Dia. = 1 mm, Sup. Gas Velo. = 332 cm/sec)	6.18
6.8. Comparison of Measured and Calculated Solid Viscosity In Fluidized Bed	6.19
6.9. Comparison of Measured and Calculated Solid Viscosity In Fluidized Bed with Central Jet	6.20
7.1. System for Simulation of Three Phase Fluidized Bed with Dimensions and Flow Conditions	7.5
7.2(a). Computed Time Average Volume Fraction Contours for Liquid Phase	7.7
7.2(b). Computed Time Average Volume Fraction Contours for Gas Phase	7.8
7.2(c). Computed Time Average Volume Fraction Contours for Solid Phase	7.9

Figure	Page
7.2(d). Photograph of Bubble Coalescence in a Liquid-Gas-Solid Fluidized Bed ($U_g=3.37$ cm/sec, $U_f=2.03$ cm/sec)	7.9
7.3. Comparison of Computational and Experimental Time Average Volume Fractions at X=2.0 cm	7.11
7.4. Comparison of Computational and Experimental Time Average Volume Fractions at X=7.0 cm	7.12
7.5. Comparison of Computational and Experimental Time Average Volume Fractions at X=11.0 cm	7.13
7.6. Bubble Formation in Three Phase Fluidized Bed at Time = 1.5 sec, for Symmetric Bed	7.14
7.7. Bubble Formation in Three Phase Fluidized Bed at Time = 2 Sec, for Asymmetric Bed	7.15
7.8. Computed Velocity Pattern in Three Phase Fluidized Bed at Time = 2 sec for Asymmetric Bed	7.17
7.9. Computed Velocity Pattern in Three Phase Fluidized Bed at Time = 2 sec for Symmetric Bed	7.18
7.10. Comparison of Experimental and Computational Results for Solid Velocity Profile at Y=7 cm	7.21
7.11. Comparison of Experimental and Computational Results for Solid Velocity Profile at Y=13 cm	7.22
8.1. Bubble Frequency Vs. Height above the Distributer at X=12.7 cm	8.3
8.2. The Image of a Bubble That Was Captured by A Recording System	8.4