



FE236924


NTIS

One Source. One Search. One Solution.

EXXON CATALYTIC COAL GASIFICATION PROCESS PREDEVELOPMENT PROGRAM. FINAL PROJECT REPORT

EXXON RESEARCH AND ENGINEERING CO.
BAYTOWN, TX

DEC 1978



U.S. Department of Commerce
National Technical Information Service

One Source. One Search. One Solution.

NTIS



**Providing Permanent, Easy Access
to U.S. Government Information**

National Technical Information Service is the nation's largest repository and disseminator of government-initiated scientific, technical, engineering, and related business information. The NTIS collection includes almost 3,000,000 information products in a variety of formats: electronic download, online access, CD-ROM, magnetic tape, diskette, multimedia, microfiche and paper.



Search the NTIS Database from 1990 forward

NTIS has upgraded its bibliographic database system and has made all entries since 1990 searchable on **www.ntis.gov**. You now have access to information on more than 600,000 government research information products from this web site.

Link to Full Text Documents at Government Web Sites

Because many Government agencies have their most recent reports available on their own web site, we have added links directly to these reports. When available, you will see a link on the right side of the bibliographic screen.

Download Publications (1997 - Present)

NTIS can now provides the full text of reports as downloadable PDF files. This means that when an agency stops maintaining a report on the web, NTIS will offer a downloadable version. There is a nominal fee for each download for most publications.

For more information visit our website:

www.ntis.gov



U.S. DEPARTMENT OF COMMERCE
Technology Administration
National Technical Information Service
Springfield, VA 22161

5360-001GF
COR.5KW-P.79

FE-2369-24
Distribution Category UC-90c

EXXON CATALYTIC COAL GASIFICATION PROCESS
PREDEVELOPMENT PROGRAM

FINAL PROJECT REPORT

T. Kalina
N. C. Nahas
Project Managers

EXXON RESEARCH AND ENGINEERING COMPANY
Baytown, Texas 77520

December, 1978

PREPARED FOR THE UNITED STATES
DEPARTMENT OF ENERGY

Contract No. E(49-18)-2369

TABLE OF CONTENTS

| | <u>Page</u> |
|--|-------------|
| ABSTRACT | v |
| LIST OF TABLES | vi |
| LIST OF FIGURES | viii |
| INTRODUCTION AND SUMMARY | x |
| 1. FLUID BED GASIFIER (FBG) STUDIES | 1 |
| 1.1 FBG Recommissioning | 1 |
| 1.1.1 Mechanical Modifications | 1 |
| 1.1.2 Updating of On-Line Data Acquisition System | 4 |
| 1.2 FBG Operations | 6 |
| 1.2.1 Startup and Baseline Operations | 7 |
| 1.2.2 Process Variable Studies | 9 |
| 1.2.3 Catalyst Recycle Operations | 10 |
| 1.2.4 Char Production Operations | 12 |
| 1.3 FBG Data Analysis | 12 |
| 1.3.1 Initial Operations | 16 |
| 1.3.2 Process Variable Studies with K_2CO_3 Catalyst | 17 |
| 1.3.3 Mixed Catalyst Operations | 18 |
| 1.3.4 Catalyst Recovery Operations | 19 |
| 1.3.5 Char Production Operations | 19 |
| 1.3.6 Comparison of FBG Data with Reactor Model Predictions | 19 |
| 1.4 Catalyst Recycle Operations | 22 |
| 1.4.1 Operations of the Catalyst Recovery Unit (CRU) | 22 |
| 1.4.2 Overall Catalyst Recycle Loop Operations | 22 |
| 1.5 Pilot Scale Secondary Catalyst Recovery | 26 |
| 1.6 FBG Scrubber Water Analysis | 28 |
| 2. BENCH SCALE STUDIES | 31 |
| 2.1 Continuous Gasification Unit (CGU) Operations | 31 |
| 2.1.1 CGU Operating Experience | 31 |
| 2.1.2 CGU Data Analysis | 35 |

| | <u>Page</u> |
|---|-------------|
| 2.2 Fixed Bed Gasification Reaction Studies | 39 |
| 2.2.1 Experimental Apparatus and Procedure | 39 |
| 2.2.2 Kinetic Data Interpretation | 43 |
| 2.2.3 Generalized Fixed Bed Model | 51 |
| 2.2.4 Alternate Catalyst Systems | 54 |
| 2.3 Recovery of Water Soluble Catalyst | 62 |
| 2.3.1 Chemical Forms of Water Soluble Potassium | 62 |
| 2.3.2 Improvement of Catalyst Recovery from the CRU | 66 |
| 2.4 Recovery of Water Insoluble Catalyst | 73 |
| 2.4.1 Mineral Matter Reactions | 75 |
| 2.4.2 Experimental Procedure | 76 |
| 2.4.3 Effect of Washing Solutions | 76 |
| 2.4.4 Effects of Temperature, Residence Time, and Calcium Loading | 81 |
| 2.4.5 Catalyst Recovery from Combusted Char | 83 |
| 2.4.6 Data Analysis | 84 |
| 2.5. Catalyst Recovery via the Formate Process | 85 |
| 3. ENGINEERING RESEARCH AND DEVELOPMENT | 88 |
| 3.1 Catalyst Source/Recovery Studies | 89 |
| 3.1.1 Commercial Sources of Potassium and Sodium Catalyst | 89 |
| 3.1.2 "Cash Flow" Analysis of Alternative Catalyst Manufacturing Processes | 92 |
| 3.1.3 Screening Evaluation of the Engel-Precht Process | 95 |
| 3.1.4 Screening Evaluation of Alternative Electrolysis Technologies | 96 |
| 3.1.5 "Cash Flow" Analysis of Alternative Catalyst Recovery Processes | 98 |
| 3.1.6 Screening Study of $\text{Ca}(\text{OH})_2$ Digestion | 101 |
| 3.2 Gasification Reactor System Studies | 104 |
| 3.2.1 Evaluation of the Incentive for Secondary Gasification | 104 |
| 3.2.2 Evaluation of Two-Stage Gasifier with Upper Drying Stage | 109 |
| 3.2.3 Impacts of Catalytic Gasifier Operating Conditions | 114 |
| 3.3 Acid Gas Removal Studies | 118 |
| 3.3.1 Evaluation of Conventional Acid Gas Removal Processes | 118 |
| 3.3.2 Evaluation of Cryogenic Fractionation for Acid Gas Removal | 119 |

| | <u>Page</u> |
|--|-------------|
| A.6 Yield Period 207 | 196 |
| A.7 Yield Period 208 | 204 |
| A.8 Yield Period 209 | 212 |
| A.9 Yield Period 210 | 220 |
| A.10 Yield Period 211 | 228 |
| A.11 Yield Period 212 | 236 |
| A.12 Yield Period 213 | 244 |
| A.13 Yield Period 214 | 252 |
| A.14 Yield Period 215 | 260 |
| A.15 Yield Period 216 | 268 |
| A.16 Yield Period 217 | 276 |
| A.17 Yield Period 218 | 284 |
| A.18 Yield Period 219 | 292 |
| APPENDIX B - PUBLICATIONS | 300 |
| B.1 Catalytic Gasification Predevelopment Research | 301 |
| B.2 Kinetics of Potassium Catalyzed Gasification | 307 |
| B.3 Catalytic Coal Gasification Process Research and Development | 327 |
| B.4 Production of SNG from Illinois Coal via Catalytic Gasification | 336 |

ABSTRACT

This report summarizes the results of work conducted on Predevelopment Research for the Exxon Catalytic Coal Gasification Process. The eighteen-month effort (July 1976-December 1977) was a coordinated program which included operation of a continuous fluidized-bed gasifier, parallel bench-scale research, and engineering studies leading to the preparation of a commercial-scale plant study design and economics for producing SNG from Illinois coal.

LIST OF TABLES

| <u>Table</u> | <u>Page</u> |
|--|-------------|
| 1.2-1 FBG Operating Summary | 8 |
| 1.3-1 Summary of FBG Material Balance Data for December, 1976, Through August, 1977. | 13 |
| 1.5-1 Recovery of Potassium Catalyst by Digestion with $\text{Ca}(\text{OH})_2$. . . | 27 |
| 1.6-1 Fluid Bed Gasifier Scrubber Water Analyses | 29 |
| 2.1-1 Material Balances for CGU Continuous Yield Periods | 36 |
| 2.1-2 Material Balances for CGU Captive Bed Yield Periods | 37 |
| 3.1-1 Principal Sources of Potassium and Sodium Salts | 90 |
| 3.1-2 Alternative Processes for Production of Potassium Carbonate | 91 |
| 3.1-3 Catalyst Manufacture Cash Flow Studies - Economic Summary . . . | 94 |
| 3.1-4 Engel-Precht Process Screening Evaluation - Breakdown of Relative Product Catalyst Cost | 97 |
| 3.1-5 Catalyst Recovery Cash Flow Studies - Economic Summary | 100 |
| 3.1-6 Screening Study of Catalyst Recovery Using $\text{Ca}(\text{OH})_2$ Digestion - Breakdown of Incremental Costs With Respect to Water Wash Only | 105 |
| 3.2-1 Incentive for Secondary Gasification - Summary of Process Basis and Heat and Material Balance | 108 |
| 3.2-2 Incentive for Secondary Gasification - Investment Breakdown . . | 110 |
| 3.2-3 Incentive for Secondary Gasification - Summary of Relative Gas Costs | 111 |
| 3.2-4 Impacts of Catalytic Gasifier Operating Conditions - Summary of Cases and Economics | 115 |
| 3.2-5 Impact of Catalytic Gasifier Operating Conditions on Gasifier Volume Requirement | 117 |

| <u>Table</u> | <u>Page</u> |
|---|-------------|
| 4.1-1 Catalytic Coal Gasification Commercial Plant Study Design - Depth of Engineering Detail | 123 |
| 4.2-1 Catalytic Coal Gasification Commercial Plant Study Design - Project Basis | 126 |
| 4.3-1 Catalytic Coal Gasification Commercial Plant Study Design - Key Process Bases for Onsites Sections | 127 |
| 4.6-1 Catalytic Coal Gasification Commercial Plant Study Design - Utilities Requirements | 141 |
| 4.7-1 Catalytic Coal Gasification Commercial Plant Study Design - Offsite Facilities Summary | 143 |
| 4.8-1 Catalytic Coal Gasification Commercial Plant Study Design - Investment for Pioneer Plant | 146 |
| 4.9-1 Catalytic Coal Gasification Commercial Plant Study Design - Economic Basis for SNG Cost | 148 |
| 4.9.2 Catalytic Coal Gasification Commercial Plant Study Design - Cost of SNG from Pioneer Plant with 100% Equity Financing . . . | 150 |
| 4.9-3 Catalytic Coal Gasification Commercial Plant Study Design - Cost of SNG from Pioneer Plant with 70% Debt/30% Equity Financing | 151 |
| A-1 Constraints Used in Reconciling FBG Operations Data | 155 |

LIST OF FIGURES

| <u>Figure</u> | <u>Page</u> |
|---|-------------|
| 0.1-1 Exxon Catalytic Coal Gasification Process | xi |
| 1.1-1 Original Fluid Bed Gasifier (FBG) Flow Plan | 2 |
| 1.1-2 Revised Fluid Bed Gasifier (FBG) Flow Plan | 3 |
| 1.1-3 FBG On-Line Data Acquisition | 5 |
| 1.3-1 Comparison of FBG Data with Reactor Model Predictions | 21 |
| 1.4-1 Catalyst Recovery Operations; Period 1 - Operation With Lime and Unblanketed Char | 23 |
| 1.4-2 Catalyst Recovery Operations; Period 2 - Operation With Lime and Blanketed Char | 24 |
| 1.4-3 Catalyst Recovery Operations; Period 3 - Operation Without Lime and Blanketed Char | 25 |
| 2.1-1 Continuous Gasification Unit (CGU) Flow Plan | 32 |
| 2.1-2 CGU Filter Vessel Flange End | 34 |
| 2.1-3 Comparison of CGU and Previous Fixed Bed Data - Extent of Steam-Carbon Reaction vs. Residence Time | 38 |
| 2.1-4 Comparison of CGU and Previous Fixed Bed Data - Approach to Equilibrium vs. Residence Time | 40 |
| 2.2-1 Schematic Diagram of Bench Scale Fixed Bed Gasification Unit | 41 |
| 2.2-2 Extent of Carbon-Steam Reaction as a Function of Residence Time | 44 |
| 2.2-3 Simplified Model for Fixed Bed Reactor in Potassium Catalyzed Steam Gasification | 45 |
| 2.2-4 Comparison of Experimental and Predicted Holding Time, θ , to Attain a Given Conversion for Model "B" | 49 |
| 2.2-5 Comparison of Fixed Bed Data With Model Prediction for Steam Feed | 52 |
| 2.2-6 Comparison of Fixed Bed Data With Model Prediction for Steam/Syngas Feed | 55 |
| 2.2-7 Gasification Rates in Fixed Bed Tests | 56 |

| <u>Figure</u> | <u>Page</u> |
|---|-------------|
| 2.2-8 Fixed Bed Gasification Runs | 58 |
| 2.2-9 Catalyst Recovery in 20 Wt% Mixed Catalyst System | 59 |
| 2.2-10 Catalyst Recovery in 15 Wt% Mixed Catalyst System | 60 |
| 2.2-11 Catalyst Recovery in 10 Wt% Mixed Catalyst System | 61 |
| 2.2-12 Catalytic Gasification of Illinois Coal | 63 |
| 2.2-13 Catalytic Gasification of Wyodak Coal | 64 |
| 2.3-1 Potassium Recovery by Cross-Current Water Washing at Low Water/Char Ratios | 67 |
| 2.3-2 Effect of Air Exposure on Potassium Recovery by Water Washing | 69 |
| 2.3-3 Potassium Recovery by Cross-Current Water Washing at High Water/Char Ratio | 70 |
| 2.3-4 Effect of Limewater Washing on Potassium Recovery | 72 |
| 2.3-5 Effect of Contact Time on Potassium Recovery with Low Water/Char Ratio | 74 |
| 2.4-1 Bench Scale Tubing Bomb Reactor | 77 |
| 2.4-2 Effect of Slurry Concentration on Potassium Recovery | 79 |
| 2.4-3 Simulation of Digestion with Downstream Solution Compositions | 80 |
| 3.1-1 Catalytic Coal Gasification Catalyst Recovery System - "Water Wash Only" Case | 102 |
| 3.1-2 Catalytic Coal Gasification Catalyst Recovery System - "Ca(OH) ₂ Digestion with Water Wash" Case | 103 |
| 3.2-1 Exxon Catalytic Coal Gasification Process with Secondary Gasification | 107 |
| 4.4-1 Catalytic Coal Gasification Commercial Plant Study Design - Schematic Flow Plan and Overall Material Balance | 133 |
| 4.5-1 Coordination Flow Plan - Catalytic Coal Gasification Commercial Plant Study Design - Onsite Facilities | 134 |

INTRODUCTION AND SUMMARY

This report covers the Predevelopment Program activities for the Exxon Catalytic Coal Gasification Process. The focus of the program was on the production of substitute natural gas (SNG) from bituminous coal. This work was performed by the Exxon Research and Engineering Company (ER&E) and supported by the United States Department of Energy under Contract No. E(49-18)-2369. The Predevelopment Program extended from July 1, 1976, through December 31, 1977.

The technical program during this predevelopment phase supports the transition to larger scale, more integrated testing in a development phase program. This section of the report first reviews the process description and results obtained prior to the predevelopment program. The objectives and results of the predevelopment program itself are then summarized.

Process Description

The Exxon Catalytic Coal Gasification Process combines the use of alkali metal salts as a gasification catalyst with a novel processing sequence which maximizes the benefits which can be derived from use of such a catalyst. The principal benefits from using an alkali metal gasification catalyst are that it increases the rate of steam gasification, reduces agglomeration of caking coals, and promotes the achievement of gas compositions closely approaching gas phase methanation equilibrium.


The process combines a relatively low gasifier temperature of about 1300°F with separation of synthesis gas ($\text{CO} + \text{H}_2$) from the product methane and recycle of the synthesis gas to the gasifier. Thus the only net products from gasification are CH_4 , CO_2 , and small quantities of H_2S and NH_3 . The resulting overall gasification reaction can be represented as follows:



Since this reaction is essentially thermoneutral, major heat input to the gasifier is not required.

A simplified flow plan for the Exxon Catalytic Coal Gasification Process is shown in Figure 0.1-1. Crushed coal is impregnated with catalyst, dried and fed via a lockhopper system to a fluidized bed gasifier which operates at about 1300°F and 500 psia. The coal is gasified with steam mixed with recycled synthesis gas, and the major gasifier product components are CH_4 , CO_2 , recycled CO and H_2 , and unconverted steam. The catalyst reduces agglomeration of caking coals and no significant tars or oils are produced. Following heat recovery and water scrubbing, the product gas is treated in a series of separation steps including acid gas scrubbing to remove CO_2 and

FIGURE 0.1-1
EXXON CATALYTIC COAL GASIFICATION PROCESS



H₂S, and cryogenic fractionation to separate product methane from synthesis gas (H₂ and CO). The synthesis gas is combined with feed steam, preheated to approximately 250°F above the gasification temperature, and recycled to the gasifier. Although there is no net heat required for the gasification reaction, some heat input is required to heat up the feed coal, vaporize residual water, and provide for gasifier heat losses.

Solid residue from the gasification step contains about 10% of the coal carbon and all of the ash and catalyst. It is sent to a catalyst recovery step in which a large fraction of the catalyst is recovered from the residue using a calcium hydroxide digestion followed by countercurrent water washing. The recovered catalyst, along with some makeup catalyst, is added to fresh coal to complete the catalyst recovery loop.

Summary of Previous Research Results

Previous Exxon-sponsored research on catalytic coal gasification was performed in bench-scale units which have the capability of operating at pressures up to 1000 psig as well as in a small pilot-scale Fluid Bed Gasifier (FBG) unit with a coal feed capacity of up to 25 lbs/hr and a maximum operating pressure of 100 psig. This pressure limitation is present because the FBG was originally built for thermal gasification work. During 1975, the FBG Pilot Plant was operated with K₂CO₃ catalyzed Illinois coal for continuous periods of up to two weeks. Good quality data were obtained for yield periods covering a wide range of operating conditions. For many yield periods, the FBG operated with synthesis gas makeup (simulated recycled) such that inlet and outlet synthesis gas rates were in approximate balance.

Close approaches to gas methanation equilibrium were demonstrated with K₂CO₃ catalyst in both bench-scale units and the FBG pilot plant. Bench-scale rate data were obtained for Illinois coal with both K₂CO₃ and Na₂CO₃/K₂CO₃ catalysts. These data were combined with analytical descriptions of fluid bed contacting to develop a first-pass computer model of a fluid bed catalytic gasification reactor.

In the area of catalyst recovery, the effectiveness of water wash for recovering about two-thirds of the catalyst was demonstrated. The forms of this recovered catalyst were identified and work was initiated on the recovery of water-insoluble catalyst. Also during this phase, engineering screening studies were carried out for commercial plants to establish preferred configurations for process flow and equipment sequencing, and to determine investments and operating costs.

Predevelopment Program Objectives

The Predevelopment Program work was divided into three major tasks. The key research objectives for each task are listed below.

Task I - Fluid Bed Gasifier (FBG) Studies With Illinois Coal

- Operate with mixed K₂CO₃/Na₂CO₃ catalyst
- Operate with recycled catalyst

Task II - Bench-Scale Studies

- Broaden data base to other coals
- Test reactivity of recovered catalyst
- Study critical factors in catalyst recovery
- Operate the small fluidized bed Continuous Gasification Unit (CGU) and fixed-bed units to obtain additional kinetic data

Task III - Engineering Research and Development

- Continue engineering screening studies
- Prepare an updated commercial plant study design

Summary of Predevelopment Program Results

The bench-scale research activities generated several significant results:

- (1) A model of the rate controlling reaction kinetics was developed. It describes gasification rate as a function of temperature, catalyst loading, and gas composition. Pressure is important only because it influences gas composition.
- (2) Early testing of mixed sodium-potassium catalyst indicated that this system would be ineffective for reducing catalyst cost.
- (3) Effort was redirected toward increasing the recovery level of the more effective potassium. This led to a preferred chemistry sequence capable of recovering more than 90% of the potassium catalyst.
- (4) Exposure of char to air was found to oxidize sulfides to sulfates and to inhibit the effectiveness of the water wash. Calcium digestion in the presence of CO was observed to convert some of the potassium sulfate to potassium formate.
- (5) Potassium sulfide was found to be catalytically active but less effective than the hydroxide and carbonate forms when the gasifying medium is pure steam. The carbonate and hydroxide forms are equal in effectiveness.
- (6) Wyoming subbituminous coal was found to be kinetically equivalent to Illinois bituminous coal in the presence of potassium catalyst.

The continuous fluid bed gasifier (FBG) was operated to simulate all commercial gasifier parameters except pressure, its effect on recycle gas rate, and the resulting effect on reaction kinetics. These parameters which were representative of expected commercial conditions include type of coal, coal size distribution, catalyst loading, reaction temperature, steam conversion, carbon conversion, fluidizing velocity, residue composition, bed density, and fluidization properties of the gasified solids. Results from FBG operations are summarized below:

- (1) The unit was used to develop fifty material balanced periods. Of these, eighteen were selected to represent a variety of process variables for detailed work-up. Unit operations were of high quality. The service factor during the last six months of operation averaged more than 70% of real time, with a one-month maximum of 96%.
- (2) FBG operations confirmed the ineffectiveness of mixed sodium and potassium catalyst.
- (3) Operations using recycled water soluble catalyst reached a recovery level of 94% of water soluble potassium (64% of total potassium). After approximately ten cycles of operation with recovered catalyst, no loss of activity nor any significant build-up of other constituents was observed. Pilot scale calcium digestion experiments demonstrated recovery of more than 90% of the total potassium from FBG residue. Recycle of catalyst at this recovery level will be a part of the development phase.

The engineering screening studies led to the following major conclusions:

- (1) The preferred form of makeup catalyst for catalytic gasification is potassium hydroxide (KOH) manufactured by electrolysis of potassium chloride (KCl). Reserves of KCl in North America are very large relative to the amounts needed. Because KOH for catalytic gasification would be produced in relatively large quantities and low purities over a long term, the cost could be significantly below the current market price.
- (2) With KOH at the current market price, calcium hydroxide digestion to recover water insoluble catalyst from spent gasifier solids is justified in addition to water washing to recover water soluble catalyst.
- (3) The addition of a secondary gasification step to raise carbon conversion to 95% from the base level of 90% provides only a marginal economic incentive.
- (4) Selective heavy glycol scrubbing for acid gas removal is somewhat lower in cost than scrubbing with non-selective hot potassium carbonate or selective refrigerated methanol.

The engineering research and development efforts culminated with the preparation of a new Catalytic Coal Gasification Commercial Plant Study Design. The process bases for the Study Design were set based on the results of the laboratory and engineering studies carried out during the Predevelopment Program. The key findings of the Study Design are:

- (1) The estimated total investment for a pioneer commercial plant feeding Illinois No. 6 coal and producing 257 billion Btu per stream day of substitute natural gas (SNG) is 1,640 million dollars (M\$).

This is for a January, 1978, cost level, at an Eastern Illinois location. A "process development allowance" and a "project contingency" are included in this estimate, consistent with standard Exxon practices.

- (2) The estimated cost of SNG produced from this pioneer gasification plant is \$6.40 per million Btu (\$/MBtu). This gas cost is an initial selling price based on 100% equity financing, a 15% DCF return, and escalation rates of 6% per year for SNG revenues and 5% per year for net operating costs. On an alternative financing basis of 70% debt/30% equity with 9% interest on debt, the comparable initial gas cost is \$4.80 per MBtu.
- (3) Several factors could reduce the SNG cost below the Study Design range of \$4.80-6.40/MBtu. These include larger plant capacities, surface-mined coals, increased government financial incentives, and future savings based on the learning experience gained from the pioneer plant and from further research and development.

The Study Design economics are believed to be a realistic prediction of the costs (in 1978 dollars) for a pioneer commercial plant. Caution must be used when comparing these economics with published estimates for other coal gasification processes. Such estimates can vary widely depending on the process, offsites, and economic bases, the investment estimate approach, and the maturity of the technology. It is expected that a consistent comparison with state-of-the-art gasification technology, which is currently in progress, will show a significant incentive for further development of the Catalytic Coal Gasification Process.