

INDEX TO TOM MICROFILM REEL 148

<u>FRAME NO.</u>	<u>TITLE</u>	<u>PAGE NO.</u>
1-20	50 Atmosphere Dehydrogenation with a Contact That can be Regenerated. Report on Results in the 100 Ccm. Furnace.	1 & 2
21-29	Testing of Contact Masses for Dehydrogenation in the 100 cc. Furnace - 408 Numbers 1-8	3
30-80	Report of the Oil Conference Held at Leuna.	4
81-88	The Calculation of Gasoline Octane Numbers by Arithmetical Means.	5
89-98	Report on the Exchange of Experience Conference Held at Foelitz from 8/7/42 to 9/5/42. Behavior of Coal Retorts with a Rising Temperature.	6
99-102	Hydrocarbon Synthesis from Carbon Monoxide and Hydrogen.	7
103	The Manufacture of Lubricating Oils from Synthetic Products.	8
104-128	DHD Experiments in the 40 Liter Furnace (3 DHD Furnace with Intermediate Reheating. 1 Refining Furnace).	9
129-133	The Deposition of "Caviar" in Liquid Phase Furnace.	10
134-146	The Influence of Temperature and Through-put in the 600 Atmosphere Aromatizing of Liquefied Bituminous Coal Middle Oil with "Terrana" Catalyst	11 & 12
147-152	Catalyst No. 7846a250.	13
153-155	Hydrocarbon Synthesis from CO and H ₂ with an Iron Catalyst According to the Emulsion Method.	14
156-158	Remarks on the Report: "An Investigation of the Hydrogenation of a Colloidal Coal Solution" by Prof. Jose Pertierre.	15
159-164	Alkylation of Unsaturated Gasolines.	16
165-171	The Processing of Synthetic Middle Oil (Dr. Michael) by Catalytic Cracking and Alkylation.	17

<u>FRAME NO.</u>	<u>TITLE</u>	<u>PAGE NO.</u>
172-174	The Production of Three Isomers--Ethyltoluene, Dimethylcyclohexane, and Ethylcyclohexane.	18
175-184	The Effect of Through-put on the "Cracking" of Bruchsal Gas Oil with HF Treated "Terrana". (Cracking and Hydrogenating, 11th Communication)	19 & 20
185-187	250 Atm. Aromatization Catalyst No. 8688 Preliminary Results.	21
188-193	Description of the Paraffin Removing Plant at the Brabog Works in Zeitz. This has been done from the point of view of equipment and of works management in order that a comparison could be made of the paraffin removing plant at Lutzkendorf.	22
194-227	The Processing of a Mixture of Ruhr Coal Tars Produced at 600 Atms. in a 10-L. Furnace and Topped at 325°C.	23 & 24
228-234	Status of Experimental Chamber SO ₄ on May 4, 1942-Production of Primary Bitumen at 700 Atms.	25
235-241	The Status to Date of Hydrocarbon Synthesis According to the Emulsion Method.	26
242-243	Current Status of Catalysts. Gas Phase Catalyst	27
244-249	Status of Experiments on Synthetic Oils	28
250-264	Catalytic Cracking of Middle Oils with Aluminum Chloride	29
265-287	Report on Experiment in Prehydrogenation of Middle Oils from Liquefied Bituminous Coal with Catalyst 7846.	30
288-294	Memo on the Conference held in Ludwigshafen on 1/30/42 About Processing of Breuxter-Tar.	31
295-317	Qualitative Comparison of Gasoline Produced from Bituminous Coal "B" Middle Oil by Cracking and by Hydrogenation.	32, 33 & 34
318-337	The Cracking of Crude Middle and Heavy Oils (Pressure and Vacuum Distillates) over Catalyst 7935. (According to Tests Carried out in a 10 L. Furnace with Gas Circulation.)	35, 36 & 37

FRAME NO.	TITLE	PAGE NO
338-347	Influence of the Degree of Hydrogenation (A. P. of Middle Oil) on the Results of Processing S-Middle Oil from Scholven by means of 8376/6434	38
348-349	Experiments in the Autoclave for the Conversion of CaCO_3 (Caviar) into CaSO_4 During the Hydrogenation of Brown-Coal from the Rhineland.	39
350-358	Notes About the Present State of the Dewaxing Plant in Zeitz.	40, 41 & 42
359-360	New TTH Tests with Catalyst 5058 and 7846.	43
361-365	Extractive Hydrogenation in a 10 Liter Furnace.	44 & 45
366-382	Present State of Performance of the Large-Scale Apparatus.	46, 47 & 48
383-394	The Use of the Aluminum Al_2O_3 -W-Ni-Prehydrogenation Catalyst 8376-7846 W250 for Various Products.	49 & 50
395-396	The Study of the Hydrogenation of Silesian Coal K1197.	51 & 52
397-508	Processing of Coal for Gasoline, Middle Oil and Heavy Oils. Processing of Silesian Coal "K1197" from the "Heinitz Mine" in a 10 Liter Furnace at 600 Atm. Producing an Excess of Heavy Oil.	53 & 54
509-510	The Caloric Effect of Coal Hydrogenation During the Production of Gasoline and Fuel Oil.	55 & 56
511-519	Experiments with H_2 - CO_2 Mixtures under DHD Conditions.	57
520-550	Properties of Some Rumanian Oils.	58
551-559	Bid for a Deasphalting Installation with a Capacity of 50,000 Tons of Vacuum Residue per Year.	59
560-564	Comparison of the Manufacturing of Gasoline Using Natural Bleaching Earth (Fuller's Earth) (6109) and Synthetic Aluminum Silicate (6752) at 600 Atm. as Catalysts.	60 & 61
565-572	Further Experiments in the Field of Aluminum-Mo-Ni-Catalysts.	62
573-582	Production of Light Gasoline.	63 & 64

<u>FRAME NO.</u>	<u>TITLE</u>	<u>PAGE NO.</u>
583-586	The U.S.A. Military Issue Specifications for Aviation Gas.	65
587-589	Silesian-Gasoline Dephenolization. Reasons for Choosing the Phenosolvan Process.	66 & 67
590-623	Prospects for Fuels with Higher Octane-Numbers in the Field of Communications.	68 & 69
624-646	Recent Tests in Preliminary Hydrogenation for the Liquefaction of Anthracite and Brown Coal, Using a Mo-Containing Catalyst in a One Liter Furnace.	70 & 71
647-658	Comparison of Dehydrogenation Catalysts 7911 (Leuna) and 7360 CH.6 (Ludwigshafen) at 10 and 25 Atm.	72
659-662	Concerning the Problem of Overloading Curves- The Limit of Error in the Determination of Overloading Curves.	73 & 74
663-664	Propylation of Anthracene for the Production of Oils with Drying Properties, According to Dr. Vierling.	75
665-670	Octane Numbers of Some Hydrocarbons.	76
671-761	Hydrogenation of Silesian Coal "K1197" of the Heinitz Mine for Gasoline and Middle Oil at 600 Atm. in a 10 Liter Furnace.	77, 78 & 79