

TOM Reel 191 Table of Contents  
 (original reel 5851-2)  
 continued from reel 190

51A

Pocket handbook of processes, equipment layout, flow diagrams, and building layouts of the Böhlen plant. Buildings 18 - 65 as follows:

<u>Page</u>	<u>Bldg.</u>	
1-2	18	List of equipment - tar chamber
3	18	Ground plan - Tar chambers 1 & 2
4	18	Flow diagram. Tar chambers
5		Piping diagram.
6	19	List of equipment - Benzine chamber
7	19	Plan layout
8	19	Flow diagram.
9	20	Intermediate storage tank. List of equipment.
10	21	Pump house - List of equipment.
11	22	Intermediate storage tank No. 2. List of equipment.
12		Flow diagram of gas scrubbers.
13-17	23	Distillation plant. List of equipment.
18	23	High pressure stabilizer
19	23	Low pressure stabilizer (Plant B.)
20	23	Flow diagram of refining plant "A"
21	23	Flow diagram of refining plant "B2"
22	23	Flow diagram of refining plant "C"
23-24	25	Fuel gas plant. List of equipment.
25		Flow diagram of Linde propane-butane plant.
26	28	Benzine scrubber - List of equipment.
27	28	Benzin scrubber - Plan layout.
28	28	Benzin scrubber - Flow diagram.
29	30&55	Piping diagram of service water

Item No.  
51A  
cont'd.

Page	Bldg.	
30	29	List of equipment. Water cooler.
30	30	List of equipment. Pump house.
30	31	Storage tank for Benzin. List of equipment.
31	32	Mixed-gas plant and pump house - List of equipment.
32	33	Fuel gas storage. List of equipment.
32	36	Nitrogen gas holder.
32	38	Gas Holder.
32	39	Waste products for railroads.
33	40	Storehouse
33	41-44	Transformers
33	45	Gas holder
33	46	Winkler water purification plant.
33	47-48	Switch-gear.
33	49	"Waschkau"
33	50	Loading of freight cars.
34	51	Blower for alkazid process.
34	52	Sulfur storage.
34	53	Garage
34	54	"Pfortnerhaus"
34	55	Water pumps and storage tanks.
35	51	Flow diagram of blowers.
36	56	Settling tank.
36	57	Settling tank.
36	58	Air raid shelter.
36	59	Scales.
36	60	Controls for steam pressure regulation.
36	61-64	Storage for foaming agents.
36	65	Storage of miscellaneous materials.
37		Flow diagram gasometer.
38		Compressed air piping diagram.
39		Piping diagram of drinking water.
40		Piping diagram of gas lines.
41		Piping diagram of phenol & waste water
42		Piping diagram of hydrogenation gas.
43		Piping diagram of steam lines.
44		Piping diagram of water lines.
45		Wiring diagram.
46		Wiring diagram for 6000-Volt lines.
47		Wiring design for 500-volt lines.
48		Wiring design for 220-volt lines for lighting.

51B

Pocket handbook of processes, equipment layout, flow diagrams, and building layouts of the Böhlen plant. Buildings 1 - 16 as follows:

Page	Bldg.	
1		Flow diagram.
2-4	1	Oxygen production plant. List of equipment.
5	1	Plan layout
6	1	Flow diagram.
7	2	Oxygen receiver
7-9	3	Water gas production - List of equipment.

Item No.51B  
cont'd,

<u>Page</u>	<u>Bldg.</u>	
10	3	Plan layout.
11	3-4	List of equipment.
12	5	List of equipment. Blowers.
13	5	Plan layout.
14	6	List of equipment. Purification towers.
15	6	Plan layout.
16-17	7	Contact plant. List of equipment.
18	7	Plan layout.
19	9	Compressors - List of equipment.
20	11	Vacuum plant. List of equipment.
21-23	9	CO <sub>2</sub> Purification. List of equipment.
24-25	9	CO Purification. List of equipment.
26	9	Layout plan.
27	9	Flow diagram - CO <sub>2</sub> scrubbers.
28	10	CO <sub>2</sub> gas holder.
29	11	Pump house. List of equipment.
30	11	Vacuum pump. List of equipment.
31-32	11	Contact plant. List of equipment.
33	11	Layout plan.
34	11	Flow diagram of liquor & pressure lines.
35	11	Flow diagram of contact plant.
36	11a	Flow diagram of vacuum plant.
37	-	Flow diagram of pump.
38-39	12	Alkazid plant. List of equipment.
40	12	Alkazid plant. Layout plan
41	12	Alkazid plant - Flow diagram.
42	13	Claus plant. List of equipment.
43	13	Claus plant. Flow diagram.
44	13-14	List of equipment.
45-48	15	Dephenolization plant. List of equipment.
49	15	Plan layout.
50	15	Flow diagram of phenol distillation.
51	15	Flow diagram of dephenolization.
52-53	16	Tar separator. List of equipment.
54	16	Tar separator. Layout plan.
55	16	Tar separator. Flow diagram.

52A

Pocket handbook of processes, equipment layout, flow diagrams, and building layouts of the "Zeitz" plant as follows:

<u>Page</u>	<u>Bldg.</u>	
1	1	Oxygen plant - Flow diagram.
2-7	1	Oxygen plant. List of equipment.
8	3/57	Water gas plant. Layout plan.
9-20	-	Winkler water gas plant - List of equipment.
21	6	Disulfurization plant. Plan layout.
22	7	Pump house. Layout plan.
23	7	Hydrogenation plant. Layout plan.
24	7	Hydrogenation plant. Section B-B; and C-C.
25-29	7	Hydrogenation plant. List of equipment.
30	9	Gas compressors.

Item No.52A  
cont'd.

<u>Page</u>	<u>Bldg.</u>	
31	9	Gas compressors - Basement.
32	9	Gas compressors - Section A-B.
33-38	9	List of equipment.
39	11	Injector pumps. Layout plan.
40-45	11	List of equipment.
46	11	Injector pumps. Layout plan.
47-49	11	List of equipment.
50	14	Hydrogen sulfide gas holder.
51-55	16	Tar separator; treatment of foul oil, etc. List of equipment.
56	17	Tar storage tank - Layout plan.
57-58	17	List of equipment.
59	18	T.T.H. Chamber. Layout plan.
60	18/19	Oven chamber. Layout plan.
61-63	18/19	List of equipment.
64	19	Gas-phase chamber. Layout plan.
65-66	19	Gas-phase chamber. List of equipment.
67-69	21	Pump house & misc. List of equipment.
70	23	Distillation plant. Plan layout.
71-72	23	Distillation plant. List of equipment.
73	26	Gas-phase hydrogenation rich-gas holder. List of equipment.
74	27	Lean-gas holder. List of equipment.
75-76	30	Pump house. List of equipment.

52B

Pocket handbook of processes, equipment layout, flow diagrams, and building layouts of the "Zeitz" plant. Buildings 31-98 as follows:

<u>Page</u>	<u>Bldg.</u>	
1-3	31/32	Benzin storage tank. List of equipment.
4	33/35	Diesel oil storage tank. List of equipment.
5	36	Work room. Plan layout of ground floor.
6	38	Nitrogen gas holder. List of equipment.
7	40	Store room.
8-10	48	CO and CO <sub>2</sub> plant. Plan layout.
11-18	48	CO and CO <sub>2</sub> plant. List of equipment.
19	54	Water filter plant. Layout plan.
20	54	Water plant - pump house. Layout plan.
21	54	Water plant - pure water receiver. Layout plan.
22	55	Settling tank. Layout plan.
23-30	54/55	List of equipment.
31	57	Bunkers, screening, & pulverizing plant.
32-35	57	List of equipment.
36-38	58	Water purification plant.
39-43	65	Waste water treatment. List of equipment.
44	57	Water purification plant.
45	70	Water works. Layout plan.
46	90	Power station.
47-71	89/90	Power station. List of equipment and products used, analyses of fuel.

Item No.

- 53 Plant rules and regulations for personnel of the Ammoniakwerke Merseburg, Leuna Works. 50-page booklet.
- 54 Cloth back photostat of piping diagram of gas products obtained from hydrogenation process. Status of Dec. 15, 1940. No. 1782(22) Ammoniakwerke Merseburg.
- ~~55 Koppers Handbook of Fuel Technology. Copyright 1937 by Heinrich Koppers GmbH. 540 pages.~~
- 56 A six page letter in English dated April 23, 1945 from Dr. Wulff, Buna-Werke, to Captain Pullen of the U.S. Army enclosing four statements as follows:
- (1) Capacity of production of Buna Werk Schkopau plant:
    - (a) Before the first air raid;
    - (b) Estimated capacity of plant in its present condition;
    - (c) Estimated capacity of plant without supply of electric current from outside.
  - (2) Products and quantities which are required per month in case (c) and naming also the factories and places where they were manufactured so far.
  - (3) List of stacks of raw materials on hand with details on how long they will last in case (c).
  - (4) Stacks of finished products on hand.
- 57 Processes used at Buna-Werk Schkopau. About 100 pages. Dates range from 1937 to 1939.  
 A rough draft probably used by some of the superintendents of the German plant at Schkopau as a ready reference in connection with plant operation. It is separated into seven portions, as follows:

### (1) Acetylene manufacture

A description is given of the various constituent phases of the manufacture of acetylene such as storage for raw materials, preparation of acetylene, purification and compression of acetylene, etc. The procedure for making acetylene seems to be the conventional process. The annual capacity of acetylene is 60 million cubic meters per year. The carbon monoxide produced as a by-product is purified and stored in a gas holder. Acetaldehyde is formed by contact with a mercury salt solution of sulphuric acid and iron sulphate. The acetaldehyde is purified by distillation to remove water, crotonaldehyde and acetylene. Considerable care has been taken to protect against fire and explosion hazard and all places where explosion might occur are blanketed with nitrogen gas. In addition, special care is taken to insure protection against lightning.

### (2) Calcium Carbide manufacture

The raw materials used in the production of calcium carbide are limestone, coke, and anthracite. The process described is conventional insofar as can be determined. Some conception of the size of the unit may be obtained by the statement made that each electrode weighs 80 tons. In this section there are appended three plans, #B2285, showing schematically the layout of the plant.

### (3) Chlorine and Sodium Hydroxide

This process is the conventional electrolytic decomposition of salt solution. The crude salt is first purified by the addition of the barium salts to remove calcium sulphate, calcium chloride, magnesium sulphate, and magnesium chloride. Approximately 36,000 tons of rock salt are used per year. The electrolysis takes place in 160 mercury cells, each having a capacity of 1200 amperes. The chlorine is water washed and passed through a packed tower using sulphuric acid. The dried chlorine is compressed. The sodium hydroxide solution is not purified but is sent to other plants. The hydrogen gas, obtained as a by-product, is stored in a gas holder.

(4) Ethylene oxide and related side reaction materials

Ethylene of 95% purity is used. Ethylene is reacted with chlorine and water to form a 5% solution of ethylene chlorohydrin. At the same time, small quantities of ethylene chloride and dichlorodiethylether are formed. The ethylene chlorohydrin is saponified with lime and is converted to ethylene oxide which is distilled off, together with the ethylene chloride and dichlorodiethylether. Conversion of ethylene oxide to diethylene glycol and side reaction products such as tri and tetraethylene glycol is effected by pressure synthesis and subsequent purification by distillation. Ethylene oxide under a blanket of nitrogen is dissolved in water and compressed in a reaction chamber to 20 atmospheres pressure. The ethylene oxide reacts with the water to form glycol and one molecule of glycol reacts with other glycol molecules to form diethylene glycol. The product is vacuum distilled and fractionated. There are appended a number of flow charts, one of them showing the formation of ethylene chlorohydrine and the various steps in the purification thereof. Another portion of this same sketch, L10067-2, shows the flow chart of the ethylene oxide apparatus. Another chart, L1767-16, shows schematically the raw materials required, and the products and by-products made in preparation of ethylene oxide.

(5) Preparation of phthalic anhydride

Phthalic anhydride is prepared by oxidizing naphthalene vapor with air, care being taken to insure that the mixture is below the explosion range. The phthalic anhydride is sublimed and melted. Impurities in the formation of phthalic anhydride are inert dust, malleic acid, benzoic acid, and phthalic acid.

(6) Preparation of Styrene

Benzene and ethylene are condensed to a raw ethyl benzene. This raw ethyl benzene is purified to remove unreacted benzene and diethyl benzene. The diethyl benzene reacts with additional quantities of benzene under the influence of catalysts to form additional quantities of ethyl benzene. The purified ethyl benzene is vaporized and is converted at a temperature of 500°C into styrene. The styrene is distilled to remove unreacted ethyl benzene. The process is divided into the alkylation, ethyl benzol distillation, the conversion (by catalysts) of ethyl benzene to styrene, and the purification of styrene. The catalyst used in the

synthesis of ethyl benzene is not mentioned except that it is stated to be sensitive to moisture. The reaction is carried out in enameled jacketed towers. The ethyl benzene is dried with solid caustic soda. In the preparation of the styrene, a by-product is formed which is merely called "furnace oil", probably resembling a heavy diesel oil. The description of the distillation and contact equipment reveals nothing unusual or novel.

#### Preparation of Aldol

Acetaldehyde is compressed and contacted with a liquid catalyst, the nature of which is not revealed. The reaction is interrupted by neutralization with small quantities of mineral acid. The inorganic salt thus formed is removed in a centrifuge. It is to be noted that the reaction chamber is stated to be made of aluminum. The butylene glycol is prepared by hydrogenation of aldol and subsequent hydrogenation of raw butylene glycol and acetaldehyde. The aldol is hydrogenated in a mixture of hydrogen and nitrogen at 300 atmospheres pressure. As stated before, the nature of the solid catalyst is not revealed. The temperature ranges between 80 and 200 degrees Centigrade. The high pressure reaction chambers are clad with copper and one of them is clad with a special steel designated as V4H. The reaction chambers are 500 mm. wide and 18 meters long. The raw butylene glycol resulting from the aldol hydrogenation is put in a stirring apparatus and is neutralized with sodium hydroxide and the resulting mass is distilled. Considerable detail is given of the re-cycling procedure and separation of the by-products.

#### (7) Preparation of vinyl chloride

Acetylene dried with solid caustic soda is brought in contact with dry gaseous hydrochloric acid. The resulting vinylchloride distills at 13.5°C. The liquid vinylchloride is transferred from storage tanks protected with nitrogen to tank cars for shipment elsewhere.

The apparent reason for the lack of details as to catalysts is probably due to the fact that these documents were ostensibly prepared for personnel who are primarily interested in safety from the standpoint of explosion, fire hazard, and other non-chemical interests.



ADDRESS: NAVY DEPARTMENT,  
BUREAU OF SHIPS

Section 341

REFER TO FILE NO.

QC/NTME(341)

NAVY DEPARTMENT

BUREAU OF SHIPS

WASHINGTON 25, D. C.



7 November 1945

Subj: Microfilm of German Technical Documents - Introductory Statement for

1. During the course of its field trips to examine German synthetic oil plants and to interrogate German technical personnel, the members of the Oil Team of the U.S. Naval Technical Mission in Europe obtained a number of technical documents for examination. Some of these documents were directly related to certain subjects in which immediate reports were desired and were incorporated in Technical Reports as microfilm appendices. Other documents, while probably of equal technical value were, due to limitations of time and translation facilities, saved for more detail study and examination. These latter documents have been indexed and micro-filmed by the Bureau of Ships to preserve the technical information therein for future use and to make possible the dissemination necessary to give each activity an opportunity to study the particular topics of interest to it.

2. There follows an index to one box of these documents, and a microfilm of the original documents in the same sequence that they appear in the index. The box number is for convenience only. The contents of this film are not to be taken as a complete record of the information obtained on any subject nor have they been grouped by topic.

3. The Bureau of Ships Research Branch, would appreciate receiving a copy of any translations that may be made of these data in order to complete its technical files.

A handwritten signature in dark ink, appearing to read "T. A. Solberg". The signature is written in a cursive style and is positioned above the typed name.

T. A. Solberg  
By direction of  
Chief of Bureau

FROM BUREAU OF SHIPS, NAVY DEPARTMENT, WASHINGTON 25, D. C.