

AD1(K) SPECIAL REELS  
UNGSTEIN DOCUMENTS

I.G. FARBENINDUSTRIE A.G. LUDWIGSHAFEN - OPPAU - TARGET 30/4.03  
TECHNISCHER PRUFSTAND OPPAU (EVACUATED TO UNGSTEIN)

REPORT NO.

INDEX - MICROFILM - REEL - 102  
(Orig. Ident. Ad1(K) 48 - (C - 64) - Part I)

F. 1	9 1	Formation of mixture and burning. The position of re- search on the diesel engine operation process	1.10.40
F. 2	103/ 1941	Second meeting of the working group dealing with two- stroke problems	May 1941
F. 3	105/ 1942	Experiences and results with an installation for investi- gating the scavenging in two-stroke engines	1942
F. 4	120/ 1944	On obtaining lubricating oils from brown coal tar	1942
F. 5	127/ 1944	The temperature behaviour of passenger car tyres in relation to speed and (tyre) pressure	25.5.44
F. 11	1150	Knock measurement with the D V L method by rate of pressure rise	18.12.39
F. 12	1250	Examination of lubricating properties by engine experiments	29.8.40
F. 13	1382	Testing of laboratory methods for the determination of lead contents in fuels	15.4.41
F. 14	1500	Identification and determination of decomposition products (in storage) of tetraethyllead in fuels	19.11.41
F. 14A	1545	Investigation of the pre-ignition reactions in Otto engines	10.1.42
F. 15	1559	Influence of various lubricating oils on the knock limit curve of fuels	
F. 16	1607	Quantitative determination of the components of quids (multi-component mixtures) by reasons of their selective absorption in infra-red spectroscopy	8.6.42
F. 17	1610	Influence of various fuels and valve overlap on engines	17.6.42
F. 18	1679	Influence of operating conditions on piston temperature	23.2.43
F. 19	1758	Charts for determining the heat content, the adiabatic limit temperature and the adiabatic heat loss between 0° and 3000°C. (Jet Propulsion)	31.12.42

REPORT NO.

F. 20 1759	Charts for determining the speed of sound, the sound pressure relations and the characteristic value of expansion and especially thrust jets up to 3000°.	
G1 201	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	16.4.41
G2 212	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	20.5.41
G3 218	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	20.8.41
G4 222	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	8.8.41
G5 223	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	19.8.41
G6 224	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	20.8.41
G7 233	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	22.9.41
G8 241	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	17.11.41
G9 242	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	1.12.41
G10 243	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	18.11.41
G11 244	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	22.11.41
G12 245	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	10.12.41
G13 250	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	24.12.41
G14 251	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	22.1.42
G15 261	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	11.5.42
G16 270	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	29.7.42
G17 271	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	31.7.42
G18 273	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	4.9.42

REPORT NO.

G19	274	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	19.9.42
G20	275	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	18.9.42
G21	283	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	28.1.43
G22	284	Investigation of knock behavior under overload conditions. (Apparently test reports of different fuels)	8.2.43
H2	401	The improvement in the use of gasoline in diesel engine	15.10.39
H3	402	Gas as diesel fuel	16.10.39
H4	403	Investigation of "Burylolen" (?Butyl Polymers)	18.10.39
H5	404	Simplification of the adjustment of the constant ignition delay with the I. G. test diesel for the evaluation of cetane numbers	6.11.39
H6	405	Ignition behavior of some fuels and lubricants	15.11.39
H7	406	Report on ignitability of gasoline	1.12.39
H8	407	Starting tests on a diesel engine	11.12.40
H9	409	Alkyl benzenes as additions to aero engine fuels	15.12.39
H10	411	Exploitation of the combustion equation (two copies)	2.1.40
H11	412	Investigation of two oils with synthetic fatty additions on their behavior in aero engines	25.1.40
H12	413	Evaluation of cetane numbers above 100	20.1.40
H14	416	Investigation of aviation fuels in the I.G. test engine	9.3.40
H15A	417	Tests of T2-100 safety fuels and a spindle oil from the "Deutschen Gasoline A.G."	1.4.40