

ItemFRAME NOS.

INDEX - MICROFILM REEL 202  
(Original designation LF - 124)

GENERAL SUBJECT

FILES OF DR. GÜNTHER OF DR. PIER'S  
STAFF AT LUDWIGSHAFEN, ON VARIOUS  
HYDROGENATION TOPICS.

Source of Documents: Griesheim Central I.G. Library

Folder Nos.           Items 1 to 37 - S1-II-D1  
                          Items 37 to 88 - S1-II-D2

Filmed by:               J I O A

Date:                    19 February 1946

<u>Item</u>		<u>FRAME NOS.</u>
1	"Gelsenberg"	1 - 9
2	6434-gasolines from various basic materials.	10 - 17
3	Aromatising with catalyst 7019 at 200 atm.	18 - 21
4	Benzination of SO <sub>2</sub> extract from synthesis middle-oil sent by Dr. Michaël.	22 - 24
5	Benzination catalysts on Terrana-ZnS basis. Catalyst tests with bituminous coal products.	25 - 27
6	Two diagrams to be used as basis for estimating 7019 aromatisation of various products.	28 - 30

<u>Item</u>		<u>FRAME NOS.</u>
7	Behavior of catalyst 3510 in 50 at dehydrogenation of pure gasolines with and without admixture of CO	- 31
8	Aromatisation of bituminous coal tar "Auguste Viktoria."	32 - 38
9	7019 catalysts: preparing of the carrier.	39 - 43
10	Catalyst Dr. Winkler-Welheim and 7019.	44 - 47
11	Manufacture of aviation gasoline from Scholven hydrogenation middle oil via aromatizing prehydrogenation.	48 - 52
12	Dehydration at 50 atm.: catalyst experiments starting from NiW.	53 - 55
13	Production of aviation gasoline from Scholven coal hydrogenation middle oil via alumina-Mo prehydrogenation.	56 - 61
14	Consumption of rarer metals in producing gasoline with fixed bed catalysts, calculated at a rate of 100 000 to gasoline p.year.	62 - 63
15	Demethylating.	64 - 65
16	Testing regenerated 6434 catalysts.	66 - 67
17	Producing gasoline from Leuna-S-Abstreifer with the new prehydrogenation catalyst 7525.	68 - 78
18	Hydrogenation of pressure distillation products from bituminous coal and coal tar "abstreifer" heavy oil over catalyst 6719 at 600 atm.	79 - 89
19	Hydrogenation of the distillation residues from gasoline dehydrogenation over catalyst which can be regenerated.	90 - 94
20	50-atm. dehydrogenation with catalyst that can be regenerated. Report on results in 100 ccm. oven.	95 - 114
21	Hydrogenation of bituminous coal tar-a-middle oils over 7846/6434 to gasoline -90°, -120°, and -150° C.	115 - 130
22	Hydrogenation of petroleum crude-oils, petroleum heavy oils and petroleum pressure distillates over fixed bed catalysts.	131 - 144

<u>Item</u>		<u>FRAME NOS.</u>
23	Causes of difference in quality of the paraffinic and naphthenic components of aromatized gasoline from coal hydrogenation.	145 - 154
24	Catalyst 7846 for prehydrogenating middle oil from Scholven.	155 - 174
25	Gas compositions in benzinization and aromatisation.	175 - 187
26	Hydrogenation of petroleum pressure distillate over fixed bed catalysts (7878) and 6434 to 87 OZ gasoline.	188 - 200
27	Processing of Russian gasoline.	201 - 207
28	Small scale experiments for processing alcohol from Oppau to 110° gasoline.	208 - 212
29	The effect of the temperature on the results of prehydrogenation with catalyst 7846.	213 - 220
30	Experiments on isomerization of butane.	221 - 223
31	On the effect of throughput, partial oil pressure and contact time on the results of prehydrogenation with catalyst 7846.	224 - 236
32	On the hydrogenation activity of alumina-tungsten-nickel catalysts of varying preparation.	237 - 242
33	The effect of the nickel content in alumina-tungsten-nickel catalysts.	243 - 244
34	Two-stage 300 at gasphase gasolines from various raw materials and with various prehydrogenation catalysts.	245 - 251
35	Di-isobutylene hydrogenation over diluted catalysts and at low pressures.	252 - 257
36	Results of the prehydrogenation of coal hydrogenation middle oil with the catalysts 5058, 7846, and 7846 W.150 at pressures between 250 and 150 at.	258 - 263
37	Low pressure splitting (50 at) of petroleum-a-middle oils	264 - 272
38	Testing new prehydrogenation catalysts.	273 - 281

ItemFRAME NOS.

39	Testing the alumina-W-Ni prehydrogenation catalyst 8376 = 7846 W-250 on various products. Part I: Scholven a-middle oils.	282 - 291
40	Testing the alumina-W-Ni prehydrogenation catalyst 8376 = 7846 W 250 on various products. Part Ia: Scholven liquid phase gasoline and middle oil.	298 - 303
41	Testing the alumina-W-Ni prehydrogenation catalyst 8376 = 7846 W 250 on various products. Part II: Gasoline plus middle oil from Leuna brown coal hydrogenation.	304 - 311
42	Testing the alumina-W-Ni prehydrogenation catalyst 8376 = 7846 W 250 on various products. Part III: Bituminous coal high temperature tar middle oils.	312 - 321
43	Testing alumina-W-Ni prehydrogenation catalyst 8376 = 7846 W 250 on various products. Part IV: Hydrogenation middle oil from Rhenanian brown coal.	322 - 337
44	Testing the alumina-W-Ni prehydrogenation catalyst 8376 = 7846 W 250 on various products. Part IVa: Liquid-phase gasoline and middle oil from Wesseling.	338 - 344
45	Testing the alumina-W-Ni prehydrogenation catalyst 8376 = 7846 W 250 on various products. Part V: Politz liquid-phase products, essentially from petroleum.	345 - 353
46	Testing the alumina-W-Ni prehydrogenation catalyst 8376 = 7846 W 250 on various products. Part VI: Products from bituminous coal low-temperature tar.	354 - 365
47	Testing the alumina-W-Ni prehydrogenation catalyst 8376 = 7846 W 250 on various products. Part VII: a / s - gasoline / - middle oil from brown coal tar (Brabag, Magdeburg.)	366 - 374
48	The behavior of acid and alkaline components of coal hydrogenation middle oil in the prehydrogenation with alumina catalysts.	375 - 379
49	Connection between the ease of benzenation of oils and their nitrogen content. (1938)	380 - 388
50	Experimental hydrogenation of 7019-B middle oil from Scholven over 8376-6434 to 87 octane gasoline.	389 - 392

<u>Item</u>		<u>FRAME NOS.</u>
51	Testing regenerated 6434 catalysts.	393 - 395
52	Benzination of 5058/7846 Mo-B-middle oil from Leuna	396 - 399
53	A formula for expressing numerically the splitting activity of benzination catalysts or the ease of benzination of oils.	400 - 403
54	Testing prehydrogenation catalysts in 30 cc lead bath ovens.	404 - 407
55	Benzination catalysts of iron fluoride on bleaching earth.	408 - 412
56	Splitting of petroleum -a- or s-middle oils over 6434.	413 - 424
57	The effect of the degree of hydrogenation (aniline point of B-middle oil) on the results of 8376/6434 hydrogenation of s-middle oil "Scholven."	425 - 435
58	The effect of sulfur in "Terrana" iron fluoride catalysts.	436 - 439
59	Testing regenerated 6434 catalysts (cf. the last report of August 6, 1942) (No. 51 of this series).	440 - 441
60	On the effect of W, V, Ni, Co, and Fe as active components on alumina prehydrogenation catalysts (two reports).	442 - 459
61	The effect of the nitrogen content of oils on their ease of benzination.	460 - 467
62	The effect of added organic nitrogen compounds on the benzination of petroleum-gasoil over catalyst 6434.	468 - 475
63	Requirements of critical metals in the gasphase for gasoline production according to the most important methods used at present.	476 - 483
64	New benzination catalysts.	484 - 497
65	Describing small-scale experiments, run on the same line as the large-scale experiment in chamber 805, and a new continuous experiment on benzination of coal hydrogenation middle oil over "Terrana" catalysts at 600 atm.	498 - 512

<u>Item</u>		<u>FRAME NOS.</u>
66	Determination of phenol in middle oil.	513 - 514
67	Testing 8376 catalysts for catalyst factories Lu and Pölitz.	515 - 519
68	Prehydrogenation of liquid-phase gasoline and middle oil from "Rheinbraun-Wesseling" over catalysts 8376/6434.	520 - 525
69	New experiments in the field of benzinization catalysts.	526 - 530
70	The effect of the nitrogen content on the ease of benzinization of oils. (cf. items 61 and 62)	531 - 533
71	A continuous experiment on prehydrogenation of bituminous and brown coal hydrogenation products over catalyst 8376 = 7846 W 250 without sulfurizing the product.	534 - 541
72	Comparing the sensitiveness to nitrogen and to changing conditions of catalysts 8797 and 6434.	542
73	Experiments with a new prehydrogenation catalyst (catalyst 9010 = 8376 + 0.3% Co <sub>2</sub> O <sub>3</sub> ).	543
74	Hydrogenation of Puertollano shale oil (Spain) and of middle oil from Puertollano shale oil over fixed bed catalysts in small ovens.	544 - 551
75	Refining liquid-phase gasolines at varying temperatures under pressure.	552 - 555
76	Conference of November 26, 1943, at Br <sup>u</sup> x on gasphase.	556 - 563
77	Hydrogenation of liquid-phase middle oil from Rumanian crude oil P 1490 over 8376/6434 or over 6434/6434.	564 - 569
78	New benzinization catalysts. Tungstenfree benzinization catalysts composed of mixtures of oxides and fluorides of Si, Al and Fe.	570 - 575
79	Benzinization of A middle oils from Hungarian crude oils.	576 - 584
80	The effect of adding sulphur on the benzinization over catalyst 6434.	585 - 599
81	The problem of converting gasoline production from the end point of 150° to the end point of 180° C. (2 reports)	588 - 589

<u>Item</u>		<u>FRAME NOS.</u>
82	Tungstenfree splitting catalysts of the type HF-treated $\text{SiO}_2$ - $\text{Al}_2\text{O}_3$ - $\text{Fe}_2\text{O}_3$ -hydroxide compounds.	590 - 599
83	The effect of temperature on the reactions occurring in the hydrogenation of coal hydrogenation middle oil over catalysts 5058, 7846 (Mo) and 8376 (= 7846 W 250).	600 - 616
84	The effect of pressure on the reactions occurring in hydrogenation of coal hydrogenation middle oil over catalyst 8376 in the range of 150-250 atm $\text{H}_2$ .	617 - 624
85	The effect of temperature on the reactions occurring in hydrogenation of coal hydrogenation middle oil over catalyst 6718.	625 - 629
86	The benzinization of fractions from prehydrogenated coal hydrogenation middle oil.	630 - 638
87	New experiments in the field of prehydrogenation catalysts, particularly of 8376.	639 - 650
88	The sulphur balance in the hydrogenation at the hydrogenation plants.	651 - 661