

## UNITED STATES PATENT OFFICE

2,645,601

TREATMENT OF PARAFFINS WITH  
ALUMINUM BROMIDEFrederick E. Frey, Bartlesville, Okla., assignor to  
Phillips Petroleum Company, a corporation of  
DelawareNo Drawing. Application June 22, 1949,  
Serial No. 100,753

13 Claims. (Cl. 196-21)

1 This invention relates to a process for the treat-  
ment of certain paraffinic materials, for example,  
a lubricating oil or a wax, to improve certain of  
its important characteristics. In one of its aspects,  
the invention relates to the treatment of a  
refined lubricating oil or a wax to lower its pour  
point employing a novel process which presents  
certain features enabling great improvements in  
quality of the treated oil product. In another of  
its aspects the invention relates to the provision  
of a novel process employing certain critical con-  
ditions essential to obtain the said improvements  
in quality or characteristics of a refined lubri-  
cating oil or wax. In still another aspect of the  
invention it relates to the effecting of certain  
novel changes within a lubricating oil or wax  
fraction employing a catalyst which is the sole  
agent now known which can cause effectuation  
of said changes. Among the characteristics of  
such a material which can be significantly im-  
proved, pour point mentioned above, and viscosity  
index especially are to be noted.

Among the objects of the invention is to pro-  
vide a process for lowering the pour point of a  
paraffinic material such as a waxy lubricating  
oil without submitting the oil to any filtration  
or other wax removal operation.

Also, among the objects of the present inven-  
tion, is to provide a process for the lowering of  
the pour point of a paraffinic material such as a  
waxy lubricating oil while at the same time mate-  
rially and significantly increasing its viscosity  
index.

Other objects and advantages are apparent  
from this disclosure and its appended claims.

The process of the present invention is pre-  
eminently applicable to the treatment of a lubri-  
cating oil containing refractory wax constituents  
to convert said constituents in a manner and to  
extent such that a substantial lowering of its pour  
point is accomplished. Accordingly the invention  
will be described making reference to the treat-  
ment of high-melting paraffin-containing stocks  
such as waxy lubricating oil base stocks of un-  
desirably high pour point.

According to the present invention a paraffinic  
material of undesirably high pour point, such as a  
waxy lubricating oil base stock, or paraffin wax,  
is admixed with a substantial quantity of alumi-  
num bromide to form an homogeneous mass  
which is then allowed to stand or is agitated for  
a number of hours depending upon the extent of  
treatment to be effected.

Preferably, before admixing the aluminum  
bromide with the oil, it is treated with an alumi-

2 num halide, an acid, or other material to remove  
undesirable constituents such as aromatic com-  
pounds and sludge-forming materials.

By effecting the treatment referred to in the  
immediately preceding paragraph, not only is the  
process of the invention rendered more effective  
to reduce the pour point of the oil, but also there  
can be observed an important increase in its vis-  
cosity index. Thus according to the invention, as  
an important feature thereof, is the combination  
of the step of treating the oil to remove un-  
desirable constituents of the nature or character  
of those just described prior to admixing the alumi-  
num bromide therewith.

To enhance the action of the aluminum bro-  
mide, a low-boiling saturated hydrocarbon mate-  
rial can be admixed with the aluminum bromide-  
oil mass. According to the invention, among the  
low-boiling hydrocarbon materials which are thus  
employed are the branched-chain paraffins with  
from four to about twelve carbon atoms, for ex-  
ample isopentane, the naphthenes with from six  
to about ten carbon atoms, for example, methyl-  
cyclopentane, or mixtures thereof. Usually about  
ten to about one hundred per cent by weight, of  
the paraffinic material, of low boiling hydrocarbon  
will be employed to assist the conversion of the  
waxy constituents of the oil by the aluminum  
bromide catalyst.

The homogeneous mass of oil, catalyst and low  
boiling hydrocarbon is allowed to stand or is agi-  
tated for a time sufficient to effect the desired  
extent of conversion. Usually a period of stand-  
ing or agitation of from about ten hours to about  
one hundred hours at a temperature in the ap-  
proximate range of 10° C. to 100° C. will be suffi-  
cient to satisfactorily lower the pour point of the  
oil. It will be understood, however, that the  
precise period of time will depend upon the tem-  
perature of the treatment, the nature of the oil  
being treated, the quantity of catalyst employed  
and even upon the exact nature and quantity of  
the low boiling hydrocarbon in the mass.

The quantity of the aluminum bromide cata-  
lyst employed is to be in the range of about ten  
to about fifty per cent by weight of the oil treated.

The exact nature of the reaction or reactions  
occurring during the conversion of the waxy con-  
stituents of the oil being treated with the alumi-  
num bromide catalyst cannot be stated. How-  
ever, it appears from a careful study of the data  
presented that isomerization of the waxy mole-  
cules plays a part in the conversion. Although  
some disproportionation appears to occur result-  
ing in the increased quantity of the low-boiling

3

hydrocarbons recovered, it is believed equally clear that the lowering of the pour point and the increases in viscosity index which have been accomplished are very likely, if not actually, due to isomerization of the waxy molecules, as stated. The use of aluminum chloride did not result in a lowering of the pour point of any of the paraffinic materials treated.

The following examples illustrate the invention. Parts are by weight. Pour points were determined by ASTM (D97-39) method.

### EXAMPLES

#### Example I

A mixture was prepared of 100 parts of a hexadecane concentrate having a freezing point (pour point) of 17.3° C., 60 parts of 95 per cent methylcyclopentane and 32 parts of anhydrous aluminum bromide. At the end of 40 hours stirring at 60-70° C., a sludge was separated which contained 2.0 parts hydrocarbon and 7.7 parts aluminum bromide. The remainder was washed free of dissolved aluminum bromide and was vacuum distilled. There was obtained 69.6 parts low-boiling hydrocarbons, including all the added methylcyclopentane, and 85.3 parts of a hexadecane concentrate boiling about 120° C. at 3-5 mm. Its freezing point (pour point) was 10.0° C., a reduction of 7.3° C. from the original.

#### Example II

A mixture was prepared of 100 parts of a hexadecane concentrate having a freezing point (pour point) of 17.1° C., 41.5 parts of isopentane and 33 parts of anhydrous aluminum bromide. At the end of 27 hours stirring at 25-35° C., a sludge was separated which contained 1.3 parts hydrocarbon and 5.0 parts aluminum bromide. The remainder was washed free of dissolved aluminum bromide and was vacuum distilled. There was obtained 61.6 parts low-boiling hydrocarbons, including all the added isopentane, and 76.4 parts of a hexadecane concentrate boiling about 120° C. at 3-5 mm. Its freezing point (pour point) was 14.9° C., a reduction of 2.2° C. from the original.

#### Example III

A mixture of 100 parts of a paraffin wax which solidified at 51-55° C. (pour point), and 27 parts of 95 per cent methylcyclopentane was stirred for 48 hours near 60° C. and then for 49 hours near 100° C. with 33 parts anhydrous aluminum bromide which was added in three nearly equal portions at 0, 23, and 30.5 hours. A sludge was separated which contained 7.1 parts of hydrocarbon and 17 parts of aluminum bromide. The remainder was washed free of dissolved aluminum bromide and was vacuum distilled. There was obtained 34.6 parts low-boiling hydrocarbons including the added methylcyclopentane and 75.6 parts of residue boiling about 136° C. at 6 mm. It solidified at 40-53° C. (pour point), an average reduction of 7° C. from the original.

#### Example IV

An SAE 20 lubricating oil from which aromatics and sludge-forming materials had been removed was treated with aluminum bromide in accordance with this invention to lower the pour point. To 55.1 parts by weight of the oil were added 22.6 parts by weight of isopentane and 22.3 parts by weight of aluminum bromide. The mixture was vigorously agitated at 90-100° F.

4

for 48 hours. The oil was then washed with water to remove dissolved aluminum bromide. The washed oil was dried with anhydrous potassium carbonate. The dried oil was topped at 250° F. and 1 mm. pressure to remove light hydrocarbons. Properties of the oil before and after the aluminum bromide treatment are shown in the following tabulation:

	Before AlBr <sub>3</sub> Treatment	After AlBr <sub>3</sub> Treatment
Pour Point, ° F. ....	35	15
Viscosity at 100° F., SUS.....	251.3	200.0
Viscosity at 210° F., SUS.....	49.84	46.92
Viscosity index.....	101	104
Yield, wt. percent.....		79

It is noteworthy that the treatment of the oil with aluminum bromide and isopentane in accordance with this invention reduced the pour point 20 degrees and increased the viscosity index.

Reasonable variation and modification are possible within the scope of the foregoing disclosure and the appended claims to the invention, the essence of which is that, under certain specific conditions, specifically and critically aluminum bromide can be employed to reduce the pour point of a paraffinic material and at the same time to increase its viscosity index.

I claim:

1. The process for lowering the pour point of a paraffinic material which comprises maintaining together said material and a low-boiling saturated hydrocarbon with a substantial proportion of aluminum bromide at a temperature in the approximate range 10° C.-100° C. for a period of time sufficient to cause a lowering of its pour point.

2. The process for lowering the pour point of a paraffinic lubricating oil which comprises maintaining together said material and a low-boiling saturated hydrocarbon with a substantial proportion of aluminum bromide at a temperature in the approximate range 10° C.-100° C. for a period of time sufficient to cause a lowering of its pour point.

3. The process for lowering the pour point of a paraffinic oil which comprises maintaining together said material and a low-boiling saturated hydrocarbon with ten to fifty weight per cent of aluminum bromide at a temperature in the approximate range 10° C.-100° C. for a period of time sufficient to cause a desired lowering of its pour point.

4. The process for treating a wax-containing paraffinic lubricating oil to reduce its pour point which comprises admixing said oil with about ten to about fifty per cent by weight of aluminum bromide, about ten to about one hundred per cent by weight of a low-boiling saturated hydrocarbon and maintaining the admixture at a temperature in the approximate range 10° C.-100° C. for a period of time in the range of from about ten to about one hundred hours and recovering an oil of lowered pour point.

5. The process of claim 1 wherein the paraffinic material is first treated to remove sludge-forming constituents therefrom.

6. The process of claim 1 wherein the paraffinic material is first treated to remove therefrom undesirable sludge-forming materials such as aromatic compounds.

7. The process of claim 1 wherein the paraffinic

5

material is first treated with an aluminum halide to remove undesirable sludge-forming constituents therefrom.

8. The process for improving the pour point of a waxy lubricating oil which comprises treating said oil with an agent effective to remove aromatics therefrom; admixing the treated oil with 10-50 parts by weight of aluminum bromide, about ten to about one hundred per cent by weight of a low-boiling saturated hydrocarbon and maintaining the admixture at a temperature in the approximate range 10° C. to 100° C. for a period of 10 to 100 hours and recovering therefrom an oil of lowered pour point.

9. The lowering of the pour point of a hexadecane concentrate which comprises admixing therewith a low-boiling saturated hydrocarbon material and a substantial quantity of anhydrous aluminum bromide, as such, and maintaining the admixture until a desirable lowering of the pour point can be observed.

10. The process of claim 9 wherein the low-boiling saturated hydrocarbon material is methylcyclopentane, the temperature is maintained in the range 60°-70° C., and the oil has an initial pour point of about 17.3° C.

11. The process of claim 9 wherein the low-boiling saturated hydrocarbon material is isopentane, the temperature is maintained in the range 25° C.-35° C. and the oil has an initial pour point of about 17.1° C.

6

12. The lowering of the pour point of a paraffin wax fraction having a pour point within the approximate range of 51° C.-55° C. which comprises admixing therewith a low-boiling saturated hydrocarbon material and a substantial quantity of anhydrous aluminum bromide, as such, and maintaining the admixture until a desirable lowering of the pour point can be observed.

13. The process of claim 12 wherein the low-boiling saturated hydrocarbon material is methylcyclopentane, the temperature is maintained at about 60° C.

FREDERICK E. FREY.

References Cited in the file of this patent  
UNITED STATES PATENTS

Number	Name	Date
1,601,406	Moody -----	Sept. 28, 1926
1,811,243	Osmer -----	June 23, 1931
2,106,010	Levi et al. -----	Jan. 18, 1938
2,468,746	Greensfelder et al. --	May 3, 1949
2,475,358	Moore et al. -----	July 5, 1949

OTHER REFERENCES

Anhydrous Aluminum Chloride in Organic Chemistry, by C. A. Thomas, Reinhold Publishing Co., New York, 1941, p. 875.

Chemical Constituents of Petroleum, by A. N. Sachanen, Reinhold Publishing Co., New York, 1945, p. 210.